

Sensors and 32-bit Microcontrollers

Freescale Tower System

Tower mechatronics board and robot

Overview

The Tower Mechatronics Board combines 32-bit computing, sensors, and actuator control into a single stand-alone board with an on-board battery supply. The Tower Mechatronics Board has a 32-bit ColdFire microcontroller with 64K of RAM, 512K of flash, and supports the full range of Freescale Xtrinsic sensors via plug-in daughter boards. The board can directly control up to eight actuators (PWM controlled RC servos) via the eight industry standard 3-pin connectors.

In addition to stand-alone operation, the Tower Mechatronic Board can be plugged into the Tower System. When plugged into the Tower System the Tower Mechatronic Board becomes a controller module, capable of interfacing with all peripheral modules available in the Tower System family to expand its capabilities.

Freescale's robot is a sensor development kit in the form of a four degrees of freedom (DOF) bipedal walking robot, controlled by the Tower Mechatronic Board. Included are simple development tools that will help you learn to write software for sensors, while making a robot walk and respond to touch, motion, vibration, tilt, and other external stimuli.

Tower Mechatronics Board Features MCF52259 32-bit ColdFire processor Control up to eight RC servos with 64K RAM, 512K flash (compatible with VEX 3 wire servos) 10 pin on-board RS232 connector USB OTG connected to MCF52259 Dual 5 volt regulators to power external **Optional** hardware plug-in for sensor daughter cards MMA7455L 3-axis accelerometer on the daughter card Power/OSJTAG MPR121 capacitive Mini-B USB touch sensor on connector main board under daughter card. 4 AA battery holder Extra output signals and on back of board touch sensor inputs



TOWER SYSTEM

Software Enablement

The Tower Mechatronic Board is supported with a full range of software. RobotSee is a scripting language as easy as BASIC, with the power of C. Using RobotSee, even people with no programming background can use the Tower Mechatronic Board to create innovative projects. When used with the Freescale Robot, RobotSee makes it easy to learn about electromechanical designs using sensors.


For the more advanced programmer, C is also supported. Using the on-board OSBDM debugger and CodeWarrior Special Suite integrated Development Studio (IDE), the board can easily be programmed in either C or assembly (C++ is available with the CodeWarrior Professional Suite). CodeWarrior Special Suite plus OSBDM is a complete debugging solution that includes flash programming, run control (source level single step) and trace.

Code samples make getting up and running easy, and both the robot and the Tower Mechatronics board are backed up with many samples in both C and RobotSee. RobotSee examples are available to make the robot walk, talk, access various sensors and even read your mind. A complete C CodeWarrior project is available with examples of how to make the robot walk, and access its sensors. The goal of the Tower Mechatronics Board and Freescale Robot is to help you create innovative projects as quickly and easily as possible.

Drivers available in the Toolkit

- General purpose 16-bit timers (GPT) input capture, output compare and PWM
 - o Fine RC servo control that is configurable for 0.25 us resolution
- PWM 8-bit controller
 - o Configurable for 7 us resolution course RC servo control
- I2C Master Mode
 - o MMA7455L 3-axis accelerometer support
 - MPR121 12 channel touch sensor support
- QSPI master mode
- · UART buffered and un-buffered
- · Analog to digital converter
- Interrupt controller
- DMA controller
- FlexCan controller
- · Periodic interrupt timers
- DMA timers

Sensor Robot Features



Development Tools		
Kit Number	Price	Includes
FSLBOT	\$199	 Tower Mechatronics Board 4 PWM controlled RC servos Leg mechanics and associated hardware Bipedal 4DOF walking robot assembly instructions Tower Mechatronics Board user guide Quick Start Guide
TWR-MECH	\$99	Xtrinsic MMA8451Q 3-axis accelerometer, MCF52259 32-bit ColdFire processor MPR121 touch sensor
LFDA8451	\$25	The LFDA8451 provides a device adapter for the Freescale MMA8451Q 14-bit 3-axis accelerometer
Documentation	on	
Document Title		Description
Tower Module Mechatronics Board User Guide		This user guide explains how to use the TWR-MECH board to write software for sensors to control the robot.
Tower Module Mechatronics Board Quick Start Guide		This quick start guide will help you use the Tower Mechatronics board as quickly and easily as possible.
Bipedal 4 Degrees of		The assembly instructions will guide you in putting together the

and motors for assembling together.

Tower Geeks Online Community

Freedom walking Robot

assembly instructions

TowerGeeks.org is an online design engineer community that allows members to interact, develop designs and share ideas with the Tower System.



physical robot pieces. The robot will ship with: brackets, screws



twitter.com/towergeeks

facebook.com/freescale

Learn More:

For more information about Freescale products, please visit www.freescale.com/robot.

Freescale, the Freescale logo and CodeWarrior are trademarks of Freescale Semiconductor, Inc., Reg. U.S. Pat. & Tm. Off. All other product or service names are the property of their respective owners. © 2011 Freescale Semiconductor, Inc.

Document Number: TWRMECHFS REV 0

