


Fiber Optics and Liquid Level Sensors Line Guide



Excellence, through every fiber. Honeywell Sensing and Control (S&C) offers fiber optic sensors manufactured with SERCOS (Serial Real-time Communication System) transmitters and receivers, duplexers, even liquid level sensors. Each fully customizable, and designed to meet and exceed harsh environmental demands.

SERCOS Transmitters and Receivers: Best for low and medium speed short-haul fiber optic links in cost-sensitive, rugged environments—from potential industrial applications to backbone in building networks.

Duplexers: Honeywell S&C's single fiber duplex modules are capable of either bi-directional data transmission or multiplexing two different wavelengths over a single optical fiber.

Liquid Level Sensors: Using the principle of total internal reflection, we've created a fast, often reliable, cost-effective solid-state sensor family.

FEATURES

DUPLEX MODULES

HOD2236-111/BBA and HOD4090-111/BBA Series.

Features: Full duplex over single fiber
 • dc to 160 MHz link bandwidth • Link budgets of 2 km [1.24 miles] or greater
 • 40 dB isolation • Other transmitter/receiver configurations, housing, and connector options available

Benefits: Pair of single fiber duplex modules allows full duplex communication over a single fiber link. Two devices per module, coupled to a single fiber via integral lenses and a 3 dB wavelength differentiating mirror, allow two corresponding duplex modules to communicate in opposing directions simultaneously and independently of each other. Used to multiplex two signals to a single fiber or where a dual fiber solution is neither possible nor economical. Fiber optic technology provides minimum data corruption and EMI/RFI immunity. Used in potential applications requiring fiber-optic medium but looking to reduce cabling

costs such as CCTV/video surveillance, data communications, test equipment, and remote sensing and control.

SERCOS TRANSMITTERS HFE7000-210 Series.

Features: Designed to work with Honeywell's high-speed receivers HFD7000-XXX and HFD7500-XXX • Super bright LED • Enhanced power output
 • Speed • Enhanced reliability • Meets SERCOS (Serial Real-time Communication System) specifications

Benefits: 650 nm wavelength provides low attenuation; integrated lens provides maximum coupling into plastic fibers. Fiber optic LED component mounted in polyimide plastic fiber-reinforced housing for mechanical stability. Plastic SMA housing delivers cost-effective module easily mounted on PCB. High-speed optical transmitter converts electrical signals into optical signals to meet data transmission requirements for factory and office automation applications. Potential

applications include harsh industrial environments, building networks, machine tool/robot control, automated industrial production lines, point-to-point links requiring a speed up to 50 Mb/s, and lower cost plastic fiber networks.

HFE7020-210 Series.

Features: Designed to work with Honeywell's high speed receiver HFE7520-2120 • Enhanced power output
 • Speed • Enhanced reliability • Meets SERCOS (Serial Real-time Communication System) specifications

Benefits: 650 nm wavelength provides low attenuation in plastic fibers. Fiberoptic LED component mounted in polyimide plastic fiber-reinforced housing for mechanical stability. Plastic SMA housing delivers cost-effective module easily mounted on PCB. High-speed optical transmitter converts electrical signals into optical signals to meet data transmission requirements for factory and office automation applications. Potential

continued on page 4

Fiber Optics and Liquid Level Sensors Line Guide

Custom solutions. Rugged performance.

Honeywell S&C offers a wide variety of fiber optic and liquid level sensors.

SERCOS Transmitters

and Receivers: Meeting all SERCOS specs and featuring SMA fiber DIP packaging — for enhanced mechanical stability and better immunity against RFI. Potential applications include machine tool and robot controls, automated lines and lower cost plastic fiber networks.

Duplexers: For potential customer-specific applications requiring a fiber-optic medium and reduced cabling costs including video surveillance, data communications, and test equipment. The modules fall into three basic configurations: 1. WDM (Wavelength Division Multiplexing) delivers full duplex data communication over a single optical fiber by multiplexing two different wavelengths of light. 2. The Active Coupler behaves as a WDM module, but uses the same wavelength of light in both directions. 3. Wave Division Combiners and Splitters can couple or divide two different wavelengths of light into, or from, a single fiber.

Liquid Level Sensors: An Optoschmitt trigger provides a digital output indicating the presence or absence of a liquid. Designed for harsh industrial environments with extremes in temperature, pressure, vibration, and shock.



Duplex Modules

	HOD2236-111/ BBA		HOD4090-111/ BBA	
	Port 1	Port 2	Port 1	Port 2
Device location	Port 1	Port 2	Port 1	Port 2
Device type	transmit 1300 nm multimode laser	receive 850 nm PIN diode	receive 1300 nm PIN diode	transmit 850 nm VCSEL
Rise/fall time	<3 ns	<3 ns	<3 ns	<3 ns
Fiber coupled power range	40 μ W to 100 μ W	—	—	200 μ W to 400 μ W
Slope efficiency	0.35 mW/mA typ.	—	—	0.2 mW/mA typ.
Forward voltage	1.2 V typ.	—	—	1.8 V typ.
Threshold current	12 mA typ.	—	—	3.6 mA typ.
Spectral bandwidth	2 nm typ.	—	—	0.85 nm max.
Response time	0.5 ns max.	3 ns max.	1 ns max.	300 ps max.
Flux responsivity	—	0.3 A/W typ.	0.50 A/W typ.	—
Dark current	—	0.05 nA typ.	2.0 nA typ.	—
Reverse voltage	—	50 V max.	20 V max.	—
Capacitance	—	1.5 pF typ.	1.5 pF typ.	—
Optical budget when used with corresponding duplexer	<10 dB	<10 dB	<10 dB	<10 dB
Connector	ST low profile	ST low profile	ST low profile	ST low profile
Operating temperature range	0 °C to 70 °C [32 °F to 158 °F]	0 °C to 70 °C [32 °F to 158 °F]	0 °C to 70 °C [32 °F to 158 °F]	0 °C to 70 °C [32 °F to 158 °F]
Mounting	PCB	PCB	PCB	PCB




SERCOS Transmitters

HFE7000-210 Series

HFE7020-210 Series

Housing style/material	plastic SMA fiber DIP	plastic SMA fiber DIP
Data rate	50 Mbps	156 Mbps
Fiber coupled output power	-10 dBm min. at 10 mA	-1.5 dBm typ. at 30 mA
Power dissipation	250 mWA	250 mW
Forward current	40 mA	50 mA
Operating temperature range	0 °C to 70 °C [32 °F to 158 °F]	0 °C to 67 °C [32 °F to 140 °F]



SERCOS Receivers

HFD7520-2XX Series

HFD7510-2XX Series

HFD7000-2XX Series

Housing style/material	plastic SMA fiber DIP	plastic SMA fiber DIP	plastic SMA fiber DIP with plastic or metal barrel
Minimum detectable signal level	-22 dBm at 650 nm	-29.5 dBm at 650 nm	-21 dBm at 660 nm
Data rate	156 Mbps max.	50 Mbps max.	16 Mbps max.
Current consumption	40 mA	40 mA (operation mode) 100 µA (standby mode)	45 mA
Supply voltage range	-0.5 V to 7 V	-0.5 V to 7 V	4.75 V to 5.25 V
Operating temperature range	-20 °C to 70 °C [-4 °F to 158 °F]	-40 °C to 85 °C [-40 °F to 185 °F]	-0 °C to 70 °C [32 °F to 158 °F]



Liquid Level Sensors

LLN Series

LLE Series

Housing material	stainless steel	polysulphone, nickel-plated brass, stainless steel
Supply voltage range	10 Vdc to 40 Vdc	5 Vdc to 12 Vdc
Supply current	60 mA max.	15 mA max.
Output	sinking	sinking
Termination	3-pin Lumberg/Brad Harrison-type connector	lead wires
Seal washer	fluorocarbon	nitrile rubber, vamac rubber
Operating temperature range	-40 °C to 125 °C [-40 °F to 257 °F]	-40 °C to 125 °C [-40 °F to 257 °F] (inclusive)

applications include harsh industrial environments, building networks, machine tool/robot control, automated industrial production lines, point-to-point links requiring a speed up to 50 Mb/s, and lower cost plastic fiber networks.

SERCOS RECEIVERS

HFD7520-2XX Series.

Features: Designed to work with Honeywell's high-speed 650 nm LED HFE 7020-210 • Often accurate, high-speed data transmission in difficult environments

- PECL voltage conversion output
- Wide dynamic range
- Enhanced reliability
- Meets SERCOS (Serial Real-time Communication System) specifications

Benefits: Monolithic chip design provides enhanced resistance to external noise and enhanced reliability. Plastic SMA housing provides cost-effective module easily mounted on PCB. Monolithic 156 Mbps receiver designed for plastic optical fiber data communication in factory automation, office machines, home automation, and LANs, especially those subject to high electromagnetic noise. Potential applications include harsh industrial environments, building networks, machine tool/robot control, automated industrial production lines, point-to-point links requiring a speed up to 50 Mb/s, and lower cost plastic fiber networks.

HFD7510-2XX Series.

Features: Designed to work with Honeywell's high-speed 650 nm LED HFE 7010-210 • Standby mode for low power dissipation • Often accurate, high-speed data transmission in difficult environments

- TTL output
- Wide dynamic range
- Enhanced reliability
- Meets SERCOS (Serial Real-time Communication System) specifications

Benefits: Monolithic chip design provides enhanced resistance to external noise and enhanced reliability. Standby mode automatically switches to low power dissipation mode when no light is input and switches back to normal operation mode when light is input, from the optical fiber. Current consumption in standby mode is approximately 1/400th that of normal current consumption. Plastic SMA housing

provides cost-effective module easily mounted on PCB. Monolithic 50 Mbps receiver designed for plastic optical fiber data communications in factory automation, office machines, home automation, and LANs, especially those subject to high electromagnetic noise. Potential applications include harsh industrial environments, building networks, machine tool/robot control, automated industrial production lines, point-to-point links requiring a speed up to 50 Mb/s, and lower cost plastic fiber networks.

HFD7000-2XX Series.

Features: Designed to work with Honeywell's high-speed 660 nm LED HFE 7000 • Enhanced mechanical stability

- Enhanced RFI/EMI/ESD shielding
- Often accurate, high-speed data transmission in difficult environments
- TTL output
- Low cost plastic version available
- Meets SERCOS (Serial Real-time Communication System) specifications

Benefits: Monolithic CMOS chip consists of large area photodiode, preamplifier with controlled gain, post amplifier, comparator, and TTL output stage. Integrated voltage regulator for easy use in many applications. On-chip controlled gain provides a wide dynamic range and low pulse width distortion. Metal receptacle provides greater mechanical stability and better immunity against RFI than plastic because electrical ground is separated from the receptacle's ground. High-speed optical receiver designed for data transmission in industrial LAN applications. Potential applications include harsh industrial environments, building networks, machine tool/robot control, automated industrial production lines, point-to-point links requiring a speed up to 50 Mb/s, and lower cost plastic fiber networks.

LIQUID LEVEL SENSORS

LLN Series.

Features: Solid-state reliability, no moving parts • 200 mA sinking output is TTL compatible • Sinking output • Fast response • Polysulphone sensor dome

- Stainless steel, high pressure housing
- IP67
- Reverse polarity and overvoltage protection

Benefits: Principle of total internal reflection creates fast, reliable, cost-effective solid-state sensor. Optoschmitt trigger provides digital output indicating presence or absence of liquid. Stainless-steel housing for extended life and easy cleaning. Quick-connect, industry-standard cable assembly for easy installation. Meets IP67 for use in harsh industrial environments with extremes in temperature, pressure, vibration, and shock such as food and beverage processing, machine tools, industrial compressors, and vending machines. Polysulphone sensor dome often suitable for potential hygiene applications.

LLE Series.

Features: Miniature size • Solid-state reliability, no moving parts • Sinking output

- Microprocessor compatible
- Very large choice of sensing media
- Cost effective
- Fast response
- Polysulphone housing
- Reverse polarity and overvoltage protection
- Short circuit and transient protection

Benefits: Photo-transistor trigger provides digital output indicating presence or absence of liquid. Internal or external mounting options for application flexibility. Miniature size for potential use in home appliances, food and beverage processing, compressors, and vending machines. Polysulphone housing often suitable for potential hygiene applications.

Warranty. Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgement or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items it finds defective. **The foregoing is buyer's sole remedy and is in lieu of all warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While we provide application assistance personally, through our literature and the Honeywell web site, it is up to the customer to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this printing. However, we assume no responsibility for its use.

For more information about Sensing and Control products, visit www.honeywell.com/sensing or call +1-815-235-6847. Email inquiries to info.sc@honeywell.com

 **WARNING**
PERSONAL INJURY

- DO NOT USE these products as safety or emergency stop devices or in any other application where failure of the product could result in personal injury.

Failure to comply with these instructions could result in death or serious injury.

 **WARNING**
MISUSE OF DOCUMENTATION

- The information presented in this catalogue is for reference only. DO NOT USE this document as product installation information.
- Complete installation, operation and maintenance information is provided in the instructions supplied with each product.

Failure to comply with these instructions could result in death or serious injury.

Sensing and Control
Automation and Control Solutions
Honeywell
1985 Douglas Drive North
Golden Valley, MN 55422 USA
+1-815-235-6847
www.honeywell.com/sensing

006729-1-EN IL50 GLO
June 2008
Copyright © 2008 Honeywell International Inc. All rights reserved.

Honeywell