



ELECTRO-OPTICAL CHARACTERISTICS AT 25°C

PARAMETERS		TEST CONDITIONS	MIN	TYP	MAX	UNITS
Active Area	45W			1		mm ²
	95W			5		mm ²
Peak Sensitivity		$V_R = 0V$		880		nm
Responsivity at 880nm			0.5	0.6		A/W
Responsivity at 750nm				0.01		A/W
Responsivity at 650nm				0.005		A/W
Spectral Bandwidth at 50%					60	
Dark Current	45W	$V_R = 5V$		0.4	2	nA
	95W	$V_R = 5V$		1	5	nA
Shunt Resistance	45W	$V_R = 10\text{ mV}$		3		Gohm
	95W	$V_R = 10\text{ mV}$		1		Gohm
Response Time	45W	$V_R = 5V, R_L = 50\Omega$		1		μsec
	95W	$V_R = 5V, R_L = 50\Omega$		1		μsec
Breakdown Voltage	45W	$I_R = 10\mu A$	20	30		V
	95W	$I_R = 10\mu A$	5	10		V
Capacitance	45W	$V_R = 0V$		170		pF
	45W	$V_R = 5V$		90		pF
	95W	$V_R = 0V$		700		pF
	95W	$V_R = 5V$		350		pF

ABSOLUTE MAXIMUM RATINGS AT 25°C

Storage and Operating Temperature Range	-55°C to 100°C
Maximum Junction Temperature	100°C
Lead Soldering Temperature (1/16" from case for 10 sec)	260°C



750 Mitchell Road, Newbury Park, California 91320
 Phone: (805) 499-0335, Fax: (805) 499-8108
 Email: sales@optodiode.com, Website: www.optodiode.com

