

Specification Status: RELEASED

Electrical Rating

Voltage: 6V_{DC} MAX
Current: 40A MAX



Insulating Material:

Cured Flame Retardant Epoxy Polymer meets
UL 94-V-O Requirements

Lead Material:

24 AWG Tin Plated Nickel Copper Alloy

Marking:

-  Manufacturer's Mark and Voltage
- RF 075 — Part Identification
-  Lot Identification (can be on back)




TABLE I. DIMENSIONS:

	A		B		C		D		E	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
mm:	--	6.9	--	11.4	4.3	5.9	7.6	--	--	3.1
in*:	--	(0.27)	--	(0.45)	(0.17)	(0.23)	(0.30)	--	--	(0.12)

TABLE II. PERFORMANCE RATINGS:

I HOLD RATED CURRENT	CURRENT RATINGS		INITIAL RESISTANCE VALUES			ONE HOUR POST-TRIP RESISTANCE STANDARD TRIP	MAXIMUM TIME TO TRIP @ 8A	TRIPPED-STATE POWER DISSIPATION
AMPERES AT 20°C HOLD	AMPERES AT 20°C		OHMS AT 20°C			OHMS AT 20°C MAX	SECONDS AT 20°C	WATTS AT 20°C
	HOLD	TRIP	MIN	TYP	MAX			
0.75	0.75	1.3	0.11	0.14	0.175	0.23	0.4	0.3

Agency Recognition:
Reference Documents:
Precedence:
Effectivity:
CAUTION:

UL, CSA, TUV recognized.
PS300
This specification takes precedence over documents referenced herein.
Reference documents shall be the issue in effect on the date of invitation for bid.
Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.

Materials Information

ROHS Compliant

ELV Compliant

Pb-Free

Directive 2002/95/EC
Compliant

Directive 2000/53/EC
Compliant

