

PERFORMANCE CHARACTERISTICS :

CURRENT RATING : 1.5A AT 20°C (FULLY LOADED)
 1A AT 70°C (FULLY LOADED)
 RATED VOLTAGE : 500V AC (CONT / CONT)
 OPERATING TEMPERATURE : -55°C TO 125°C
 CONTACT RESISTANCE : 25mΩ MAX.
 INSERTION FORCE : 0.75 N MAX / CONT
 EXTRACTION FORCE : 0.15 N MIN / CONT
 INSULATION RESISTANCE : 10⁴ MΩ MIN.


NOTES :

- UL APPROVED WITH USR AND CNR.
- MEASURED AT THE BOTTOM.
- MATERIAL CONTACT : PHOSPHORBRONZE.
HOUSING : LCP 30% GLASS-FILLED.
- CONNECTOR PRINTED WITH P/N AND DATE CODES.
- FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN MATING SIDE.)
- 4 = LEVEL 1 (5.30)
5 = LEVEL 2 (6.80)
6 = LEVEL 3 (8.30)
- 'HM2J09PE5110' LEAD FREE INDICATOR : LF = LEAD FREE
- PERFORMANCE LEVEL INDICATOR (Ref DWG No BS,C ,201844,003)
- FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS,A ,201572,001
- THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

LOADING PATTERN : MATING SIDE

F	0	0	0	0	0	0	0	0	0	0	0	0	0	0
E	4	4	4	4	4	4	4	4	4	4	4	4	4	4
D	4	4	4	4	4	4	4	4	4	4	4	4	4	4
C	4	4	4	4	4	4	4	4	4	4	4	4	4	4
B	4	4	4	4	4	4	4	4	4	4	4	4	4	4
A	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Z	0	0	0	0	0	0	0	0	0	0	0	0	0	0
I	2	3	4	5	6	7	8	9	10	11				

PCB HOLE LAY-OUT



www.fciconnect.com		surface - ISO 1302	tolerance std ISO 406 ISO 1101	projection mm
		TOLERANCES UNLESS OTHERWISE SPECIFIED		
Dr N.Otto	2000-04-28	ANGULAR	0.X ±0.2	size A3 Scale 1/1
Eng N.Otto	2000-04-28	LINEAR	0.XX ±0.1	
Chr Alex Babu	2008-04-24	0° ±1°	0.XXX ±0.05	ECN 111-0044
Appr Alex Babu	2008-04-24	Product family	MILLIPACS	Spec ref -
title MPACS RA HDR type C, not shielded			dwg no BSC202767012	Rev. H
catalog no HM2J09PE5110----			CUSTOMER COPY	sheet 1 of 1

rev	ecn no	dr	date
H	111-0044	GT	2011-02-28
C	105-0108	AB	2005-06-29
D	106-0107	AB	2006-07-12
E	107-0034	AB	2007-03-07
F	108-0050	AB	2008-04-24
G	110-0098	GT	2010-04-19