





Tous droits strictement réservés. Reproduction ou communication de quelque manière que ce soit sans l'autorisation écrite de la direction des ventes est formellement interdite. Propriété de F.C.I. Droits de reproduction F.C.I.



All rights strictly reserved. Reproduction or issue to third parties in any form or by any means without written authority from the proprietor. Property of F.C.I. Copyright F.C.I.



**PERFORMANCE CHARACTERISTICS**

CURRENT RATING 1.5A AT 20°C (FULLY LOADED)  
 1 A AT 70°C (FULLY LOADED)  
 RATED VOLTAGE : 500 V AC (CONT /CONT)  
 OPERATING TEMPERATURE : -55°C TO 125°C  
 CONTACT RESISTANCE 20 MΩ MAX  
 INSERTION FORCE : 0.75N MAX/CONT  
 EXTRACTION FORCE : 0.15N MIN/CONT  
 INSULATION RESISTANCE : 10<sup>4</sup> MΩ MIN

NOTES 1. " " LEAD FREE INDICATOR : LF=LEAD FREE  
 " " PERFORMANCE LEVEL INDICATOR (REF DWG NO.BSC .201844.003)

- THIS PRODUCT IS CSA APPROVED. THIS PRODUCT IS UL RECOGNIZED.
- FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING :BS.A.201572.001
- THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

Material		Spec ref	
Mat code		tolerance 1DEC 2 DEC 3 DEC 4 DEC ANGLES 1° 45° 90°	
Heatreat		projection	
Plating/Finish		MM	
Dr	M.Fret	31-10-97	size A4
Eng		Product family	Scale 2.000
Chr		Model Name	HM2S30PE5101
Appr		Model Revision	ECN
rev	ecn no	dr	date
A	CONVERSION	KN	14-09-01
B	104-0114	ALEX	27.11.04
C	D605-029	Kason	05-08-05
D	D606-025	Kason	06-27-06
E	D610-0110	NZ	2010-9-3
Title		BSC201907010	
MILLIPACS 2/TYPE C(W/O LOCK.PEG) SHIELDED		Rev. E	
Pro/E file	catalog no	HM2S30PE5101----	CUSTOMER DRAWING
		sheet 1 of 1	