



ASSEMBLED VIEW
(FOR REFERENCE ONLY)

- △ MATERIALS:
 BODY, COVER AND LOCKING SPRING INSULATOR—
 FERROUS METAL, BAKELITE, WHITE.
 REAR SHELL UPPER AND BOTTOM BEIGE, WHITE.
 WITH 0.005 [0.002] MINIMUM NICKEL PLATED OVER
 LOCKING SPRING MINIMUM COPPER UNDERPLATE.
 THICK STAINLESS STEEL.
 FERRULE—0.530-015, 1.0200±.0006 STEEL,
 WITH 0.005 [0.002] MINIMUM NICKEL PLATED OVER
 CABLE CLAMP—0.534-005 02-01-0021 THICK STEEL,
 WITH 0.005 [0.002] MINIMUM NICKEL PLATED OVER
 SCREW—STEEL WITH 0.005 [0.002] MINIMUM NICKEL
 PLATED OVER 0.0013 [0.0005] MINIMUM COPPER
 UNDERPLATE.
 ALL DIMENSIONS ARE MAXIMUM UNLESS OTHERWISE
 SPECIFIED.
- △ KIT SHIPPED NOT ASSEMBLED.

REV	DATE	DESCRIPTION	BY	CHKD	APP'D
AR	84	RELEASED/NPR C89-100			
B		OBSELETE PER EC 0020-0304-94			
C		REVISED ECR-08-018717			

REV	DATE	DESCRIPTION	BY	CHKD	APP'D
AR	84	RELEASED/NPR C89-100			
B		OBSELETE PER EC 0020-0304-94			
C		REVISED ECR-08-018717			

REV	DATE	DESCRIPTION	BY	CHKD	APP'D
AR	84	RELEASED/NPR C89-100			
B		OBSELETE PER EC 0020-0304-94			
C		REVISED ECR-08-018717			

REV	DATE	DESCRIPTION	BY	CHKD	APP'D
AR	84	RELEASED/NPR C89-100			
B		OBSELETE PER EC 0020-0304-94			
C		REVISED ECR-08-018717			

REV	DATE	DESCRIPTION	BY	CHKD	APP'D
AR	84	RELEASED/NPR C89-100			
B		OBSELETE PER EC 0020-0304-94			
C		REVISED ECR-08-018717			

CAD DRAWINGS
 THE DIMENSIONS AND CONTROLS ON THIS DRAWING ARE UNPUBLISHED. RELEASED FOR PUBLICATION. THIS DRAWING IS UNPUBLISHED. © Copyright 1987 by AMP Incorporated. All International Rights Reserved. 19

METRIC

DO NOT SCALE PRINT.
 UNLESS SPECIFIED (INCHES)
 TOLERANCES: ± .001
 5 P.C. DEC ± .001
 ANGLES ± .5°
 FINISH: Δ

AMP INCORPORATED
 HARTFORD, CT 06183

CASE KIT, SHIELDED, 75',
 CHAMP .050, SERIES II ©

SIZE: 114-5136
 SCALE: 4:1

DRAWING NO: 175930
 SHEET: 1 OF 1