


1. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
2. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.6mm THICK CIRCUIT BOARD.

PT. NO.	PARTS NAME	MATERIAL	Q'TY	NOTE
1	HOUSING	PBT RESIN GLASS REINFORCED (UL94V-0)	1	COLOR : BLACK
2	SLIDER		1	
3	CONTACT	PHOSPHOR BRONZE	n	PLATING : Sn Ni UNDER PLATED (LEAD FREE)

n : NO. OF CONTACTS

mat'l. code		surface 58 ISO 1302 ✓		tolerance ISO 406 ISO 1101		projection mm		product family 58KF		CODE JP	
ltr	ecn no	dr	date	tolerances unless otherwise specified		mm		title 1.25mm SPACING FPC/FFC CONNECTOR (Cat. No. SLD__S-1LF)			
A	J05-0435	H.T	7/8/05	angles	linear	±0.3					
B	J05-0733	H.T	10/28/05								
C	J06-0503	H.T	11/28/06								
				dr		11/28/06					
				enr		11/28/06		dwg no		sheet 1 of 1 size	
				chr		11/23/06		JSA 96550		A4	
				app		11/28/06		type		Product Customer Drawing	
sheet index	revision	C									Rev
	sheet	1									C

SC-SLDD2 form: A4 JSA96548 96549 91823



FCIconnect.com

Copyright FCI.