



1. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
2. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.6mm THICK CIRCUIT BOARD.

| PT. NO. | PARTS NAME | MATERIAL | Q'TY | NOTE |
|---------|------------|---|------|---|
| 1 | HOUSING | PBT RESIN GLASS REINFORCED (UL94V-0) | 1 | COLOR : BLACK |
| 2 | SLIDER | | 1 | |
| 3 | CONTACT | PHOSPHOR BRONZE | n | PLATING : Sn Ni UNDER PLATED (LEAD FREE) |

n : NO. OF CONTACTS

| | | | | | | | | | | | | |
|-------------|----------|--------------------|-----------|---------------------------------------|--------|------------|--|----------------------------------|--|---------|--|--------|
| mat'l. code | | surface ISO 1302 ✓ | | tolerance ISO 406 ISO 1101 | | projection | | product family 58KF | | CODE JP | | |
| ltr | ecn no | dr | date | tolerances unless otherwise specified | | mm | | title | | | | |
| A | J05-0435 | H.T | 7/8/'05 | angles | linear | ±0.3 | | 1.25mm SPACING FPC/FFC CONNECTOR | | | | |
| B | J05-0733 | H.T | 10/28/'05 | | | | | (Cat. No. SLD__S-2LF) | | | | |
| C | J06-0503 | H.T | 11/28/'06 | | | scale X | | dwg no sheet 1 of 1 size | | | | |
| | | | | dr <i>H. Sridharan</i> 11/28/06 | | | | JSA 96552 A4 | | | | |
| | | | | enr <i>H. Sridharan</i> 11/28/06 | | | | type Product Customer Drawing | | | | |
| | | | | chr <i>R. Sridharan</i> 11/28/06 | | | | | | | | |
| | | | | app <i>S. Sridharan</i> 11/28/06 | | | | | | | | |
| sheet index | revision | C | sheet | 1 | | | | | | | | Rev. C |

SC-SLD02 form: A4 JSA96548 96551 91823

1

2



FCIconnect.com

Copyright FCI.

