



1. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
2. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.6mm THICK CIRCUIT BOARD.

PT. NO.	PARTS NAME	MATERIAL	Q'TY	NOTE
1	HOUSING	PBT RESIN GLASS REINFORCED (UL94V-0)	1	COLOR : BLACK
2	SLIDER		1	
3	CONTACT	PHOSPHOR BRONZE	n	PLATING : Sn Ni UNDER PLATED (LEAD FREE)

n : NO. OF CONTACTS

mat'l. code		surface ISO 1302 ✓		tolerance ISO 406 ISO 1101		projection		product family 58KF		CODE JP	
ltr	ecn no	dr	date	tolerances unless otherwise specified		mm		title 1.25mm SPACING FPC/FFC CONNECTOR (Cat. No. SLD__R-2LF)			
A	J05-0435	H.T	7/8/'05	angles	linear	±0.3		dwg no sheet 1 of 1 size			
B	J05-0733	H.T	10/28/'05					JSA 96551 A4			
C	J06-0503	H.T	11/28/'06			scale X		type Product Customer Drawing			
sheet index		revision sheet		dr		engr		chr		appd	
1		C 1		K. Showk 11/28/06		S. S. S. 11/28/06		S. S. S. 11/28/06		1	

SC-SLD02 JSA96548 96552 91823 form: A4



FCIconnect.com

Copyright FCI.

