

USB-B, USBR-B, USBC SERIES

STANDARD & RUGGED USB INTERFACES

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?USB-B or www.samtec.com?USBR-B

Insulator Material:

High Temperature Thermoplastic

Contact Material:

Phosphor Bronze

Shell Material:

Brass

Plating:

Gold on Contacts, Nickel on Shell, Tin on Tails

Operating Temp Range:

-50°C to +85°C

Current Rating:

1A per contact

Voltage Rating:

30 VAC

Contact Resistance:

30 mΩ max

Cycles:

1500 (maximum number of cycles tested)

Packaging:

Packaged and shipped in Bulk Packaging Trays; Trays suitable for automation are available upon request.

RoHS Compliant:

Yes

Lead-Free Solderable:

USB-SM=Yes

USB-TH=Yes

(Wave Solder only)

USBR=Yes (Wave Solder only)



TYPE

B

S

PLATING

COLOR

TERMINATION

OTHER OPTION

USB

= Standard Connector

USBR

= Increased Retention Connector (Complies with Class 1, DIV II minimum withdrawal requirement of 15N.)

-F

= Gold Flash on Mating Area, Tin on Tails

-S

= 30μ" (0.76 μm) Gold on Mating Area, Tin on Tails

-B

= Black (USB only)

-W

= White (USB only)

-O

= Orange (USBR only)

-TH

= Through-hole

-SM

= Surface Mount



-VT

= Vertical Top Entry (USBR Series only)

-TR

= Tape and Reel Packaging (-SM only)

MATING / UNMATING FORCE (100 CYCLES)		
SERIES	MATING	UNMATING
USB	5.3 (23,59N)	6.1 (27,15N)
USBR	11.8 (52,51N)	11.5 (51,18N)



SPECIFICATIONS

For complete specifications see www.samtec.com?USBC

Insulator Material:

Glass Filled Thermoplastic

Contact Material:

Copper Alloy

Shell Material:

Cold Rolled Steel (0,30mm) .012" thickness

Plating:

Gold on Contacts, Nickel on Shell, Tin on Tails

Operating Temp Range:

0°C to +40°C

Current Rating:

1.0A per contact

Voltage Rating:

30 VAC (R.M.S.)

Contact Resistance:

30 mΩ max

Minimum Cycles:

5000

RoHS Compliant:

Yes

USBC

END NO. 1

END NO. 2

B

B

PLATING

WIRE LENGTH

Mates with:
MUSB, USB,
USBR

-MA
= USB Mini A
Type Plug


-AM
= USB-A
Type Plug

-MB
= USB Mini B
Type Plug

-BM
= USB-B
Type Plug
(N/A with -MA)

-S
= 30μ" (0.76μm)
Gold on contact area

-1
= (1m) 39.37"
-2
= (2m) 78.74"
-3
= (3m) 118.11"



Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC SILICON VALLEY • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329
SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0
SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 6890337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292 SAMTEC ISRAEL • Tel: 972-3-7526600
SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-61103766 SAMTEC TAIWAN • Tel: 886-2-2735-6109
SAMTEC HONG KONG • Tel: 852-2600-9858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9512 7747 SAMTEC SOUTH AFRICA • Tel: 27 11 452 8112