5650404 - 5 Product Details



5650404 - 5

Eurocard Type C

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- ? Type C Connectors
- ? Receptacle
- ? Number of Positions = 150
- Rows Loaded = A, B, C
- ? Terminate To Printed Circuit Board

<u>View all Features</u> | <u>Find Similar</u> Products



Quick Links -

This Product

Check Pricing &
Availability
Search for Tooling
View Mating
Products (4)
Product Feature
Selector
Contact Us About

Documentation & Additional Information

Product Drawings:

ASSEMBLY, RECEPTACLE, EUROCARD, TYPE C, LEAD -FREE, 1... (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

? None Available

Application Specifications:

2 Eurocard Connectors Types B,C,M,Q,R, & Enchanced Typ... (PDF English)

Instruction Sheets:

? None Available

CAD Files:

? None Available

Additional Information:

Product Line Information

Related Products:

- ? Tooling
- ? Mating Products (4)

List all Documents

Product Features

es (Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Type C Connectors
- ? Gender = Receptacle
- ? Number of Positions = 150
- ? PCB Retention Feature = No
- ? PCB Mount Angle = Vertical
- ? Post Type = Solder Post
- ? Size = Expanded
- ? Make First / Break Last = No
- ? DIN Level = II
- ? Mounting Ears = With
- ? Toolless (Flat Rock) = No
- ? Color = Gray

Termination Related Features:

- ? Termination (Solder) Post Length (mm [in]) : 2.49 [0.098]
- ? Solder Tail Contact Plating = Tin

Body Related Features:

- ? Rows Loaded = A, B, C
- ? Contact Cross Section (mm [in]) = 0.30 x 0.61 [.012 x .024]

Contact Related Features:

- ? Contact Material = Copper Alloy
- Contact Mating Area Plating Material = DIN 41612 Class 2

Housing Related Features:

- ? Housing Material = Polymer
- ? Housing Flammability Rating = UL 94V -0

Industry Standards:

- ROHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- ? Flux Tight Coating = Without
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- ? Terminate To = Printed Circuit Board
- ? High Temperature Housing = No

Other:

? Brand = AMP

Provide Website Feedback | Contact Customer Support