Our commitment. Your advantage.

roducts Docur

Occumentation


Posouroos

My Account

Customer Suppor

Home > Products > By Type > D Subminiature > Product Feature Selector > Product Details

5174681 - 7 Product Details



Active


.050 Series Board Mount Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance

Product Highlights:

- ? Connector
- ? Receptacle
- ? Number of Positions = 68
- Not Shielded
- Without Mating Connector Lock

<u>View all Features</u> | <u>Find Similar</u> <u>Products</u>



Quick Links

Check Pricing &
Availability
Search for Tooling
Product Feature
Selector
Contact Us About
This Product

Documentation & Additional Information

-7

Product Drawings:

5174681

PLUG ASSY VERTICAL (W/KINK) AMPLIMITE .050 SERIES I ...
(PDF, Japanese)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

? None Available

Application Specifications:

? None Available

Instruction Sheets:

? None Available

CAD Files: (CAD Format & Compression Information

- 2D Drawing (DXF, Version O)
- 2 3D Model (IGES, Version O)
- ? 3D Model (STEP, Version O)

Additional Information:

? Product Line Information

Related Products:

? Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Connector
- ? Gender = Receptacle
- ? Number of Positions = 68
- ? Shielded = No
- ? Mating Connector Lock = Without
- ? Mount Angle = Vertical
- ? PCB Polarization = Without
- ? PCB Retention Feature = Yes
- ? Rails = Without
- ? Shell Type = All Plastic
- ? Product Series = Series I

Termination Related Features:

? Termination (Solder) Post Length (mm [in]) = 3.10 [0.122]

Body Related Features:

- ? PCB Retention Method = Retention Solder Tails
- Post Plating = Tin over Nickel

Contact Related Features:

List all Documents

- ? Contact Mating Area Plating Material = Gold (8)
- ? Contact Material = Phosphor Bronze

Housing Related Features:

- ? Housing Material = Thermoplastic
- ? Housing Flammability Rating = UL 94V -0
- ? Housing Color = Black

Industry Standards:

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Other:

? Brand = AMP

Provide Website Feedback | Contact Customer Support