

Direct Links ...

- Cross Reference
- RoHS/LF P/N search
- Document & Drawing search
- Application tooling

Services ...

- Contact us
- Distributor list
- Pricing request
- Order samples

Literature ...

- Brochures & catalogs
- Product documentation
- Technical library

8638PSS2006

[Assistant](#) [Add to Favorites](#)



8638PSS2006 - D-Subminiatures

Power contacts 8638 Socket Solder Bucket 20 A, >500 Cycles

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More


- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)
- [Check distributor stock](#)

MATURE

[Customer Drawing](#)

Electronics division

Alternate Products

 [8638PSS2006LF](#)
Power contacts 8638 Socket Solder Bucket 20 A, >500 Cycles

Download document

Literature

- [> D-Subminiature Brochure](#)
- [> Connector Overview Brochure](#)

Application Tooling

- [> Asia Pacific Application Tooling](#)
- [> Americas Application Tooling](#)
- [> Europe Application Tooling](#)

Specifications

General	Dimensional	Electrical	Mechanical	Physical
General				
Contact type				Power
Gender				Socket
Product Type				Contact
Termination Style				Solder Bucket
Dimensional				
Length (Overall)				22 mm max
Size (Wire)				12 AWG
Strip length (Wire)				7 mm
Diameter A (Inner)				2.8 mm
Diameter B (outer)				3.65 mm
Electrical				
Current rating				20A
Mechanical				
Durability (Mating cycles)				> 500 Cycles
Physical				
Plating (Contact)				Gold over Nickel
Color (Clip)				Red
Plating (Termination)				Tin-Lead over Nickel