

Direct Links ...

- Cross Reference
- RoHS/LF P/N search
- Document & Drawing search
- Application tooling

Services ...

- Contact us
- Distributor list
- Pricing request
- Order samples

Literature ...

- Brochures & catalogs
- Product documentation
- Technical library

Start > [Search=8638PSS4006*](#) > **8638PSS4006**

8638PSS4006

[Assistant](#) [Add to Favorites](#)



8638PSS4006 - D-Subminiatures

Power contacts 8638 Socket Solder Bucket 40 A, >500 Cycles

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)
- [Check distributor stock](#)

MATURE

[Customer Drawing](#)

Electronics division

Alternate Products



[8638PSS4006LF](#)
Power contacts 8638 Socket Solder Bucket 40 A, >500 Cycles

Download document

Literature

- [> D-Subminiature Brochure](#)
- [> Connector Overview Brochure](#)

Application Tooling

- [> Asia Pacific Application Tooling](#)
- [> Americas Application Tooling](#)
- [> Europe Application Tooling](#)

Specifications

General	Dimensional	Electrical	Mechanical	Physical
General				
Contact type				Power
Gender				Socket
Product Type				Contact
Termination Style				Solder Bucket
Dimensional				
Length (Overall)				22 mm max
Size (Wire)				8 AWG
Strip length (Wire)				7 mm
Diameter A (Inner)				4.4 mm
Diameter B (outer)				5 mm
Electrical				
Current rating				40A
Mechanical				
Durability (Mating cycles)				> 500 Cycles
Physical				
Plating (Contact)				Gold over Nickel
Color (Clip)				Blue
Plating (Termination)				Tin-Lead over Nickel