

This document was generated on 02/25/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0430200200

Status: Active
Overview: microfit 30

Description: 3.00mm (.118") Pitch Micro-Fit 3.0™ Plug Housing, Dual Row, with Panel Mount Ears,

Halogen-Free, 2 Circuits, Glow Wire Compatible

Documents:

3D Model Test Summary TS-43045-001 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-43045 (PDF)

Agency Certification

CSA LR19980 TUV R72081037 UL E29179

General

Product Family Crimp Housings Series 43020

Application Power

Comments Converted to Halogen-Free and Glow Wire Compatible

Material on 9/21/2010

Overviewmicrofit 30Product Literature Order NoUSA-106Product NameMicro-Fit 3.0^{TM}

Physical

Circuits (maximum) 2 Circuits Detail Color - Resin Black Flammability 94V-0 Male Gender Glow-Wire Compliant Yes Lock to Mating Part Yes Material - Resin Nylon Number of Rows 2 Packaging Type Bag Panel Mount Yes

Pitch - Mating Interface 3.00mm (.118")
Pitch - Termination Interface 3.00mm (.118")

Polarized to Mating Part Yes Stackable No

Temperature Range - Operating -40°C to +105°C

Electrical

Current - Maximum per Contact 5A


Material Info

Reference - Drawing Numbers

Product Specification PS-43045, RPS-43045-003, RPS-43045-004

Sales Drawing SDA-43020-****
Test Summary TS-43045-001

This document was generated on 02/25/2011



EU ROHS
ELV and ROHS
Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

43020 Series

Mates With

43025 Micro-Fit 3.0™ Receptacle Housing

Use With

Micro-Fit 3.0™ Crimp Terminal, Male

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION