


Product Details for 3 -1478978 -1



3-1478978 -1

[Active](#)

SMA/QMA RF Connectors

[RoHS Compliant \(Statement of Compliance\)](#)

Product Highlights:

- ? Connector
- ? Jack Receptacle
- ? Connector Type = SMA
- ? Terminate To Printed Circuit Board
- ? Body Style = Right Angle

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [SMA RIGHT ANGLE PCB SOCKET RECEPTACLE](#) (PDF, English)

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? [Product Type](#) = Connector
- ? [Gender](#) = Jack Receptacle
- ? [Connector Type](#) = SMA
- ? [Body Style](#) = Right Angle
- ? [PCB Mount Angle](#) = Right Angle
- ? [Body Material](#) = Brass
- ? [Body Finish](#) = Gold
- ? [Center Contact](#) = With
- ? Grade = Commercial
- ? Dielectric Material = Delrin
- ? PCB Retention Method Feature = Solder Pin
- ? Solder Terminal = With
- ? Sealed = No
- ? Isolated = No

Mechanical Attachment:

- ? [Panel Attachment](#) = Without
- ? Impedance (?) = 50
- ? Panel Cutout = 1 x 1.4 + 4 x 1.5

Electrical Characteristics:

- ? Frequency = DC to 6 GHz

Body Related Features:

- ? [Length \(mm \[in\]\)](#) = 13.50 [0.532]
- ? Polarized = No

Contact Related Features:

- ? Center Contact Material = Brass
- ? Center Contact Plating = Gold

Industry Standards:

- ? Government/Industry Qualification = No
- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Converted to comply with RoHS directive

Conditions for Usage:

- ? [Terminate To](#) = Printed Circuit Board
- ? Operating Temperature (Max.) (°C) = 165

Packaging Related Features:

- ? Packaging Quantity = 100

Other:

- ? Brand = Greenpar