

## 228435-1 Product Details



**228435-1**

TE Part Number: 228435-1

Active

Add to Part List

### SMB RF Connectors

[Not EU RoHS or ELV Compliant](#) ([Find RoHS Compliant Alternates](#))

#### Product Highlights:

- Connector
- Jack
- Standard
- Terminate To Printed Circuit Board
- Coupler Style = Quick Connect/Disconnect

[View all Features](#) | [Find Similar Products](#)

Live Product Chat

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)
- [Request Samples](#)

**NEW!**

### Documentation & Additional Information

#### Product Drawings:

- [JACK, RIGHT ANGLE, PCB, COMMERCIAL SMB](#) (PDF, English)

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- [AMP\\* SMB MIL-TYPE 50-OHM AND 50- AND 75-OHM COMMERCIAL...](#) (PDF, English)

#### CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version C)
- [3D Model](#) (IGES, Version C)
- [3D Model](#) (STEP, Version C)

[List all Documents](#)

#### Additional Information:

- [Product Line Information](#)

#### Additional Product Images:

- [PCB Layout](#)

#### Related Products:

- [Tooling](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- [Product Type](#) = Connector
- [Gender](#) = Jack
- Connector Series = Standard
- [Body Style](#) = Right Angle
- [Grade](#) = Commercial
- [PCB Mount Angle](#) = Right Angle
- PCB Mount Style = Thru Hole
- Dielectric Material = TEFLON

#### Mechanical Attachment:

- [Panel Attachment](#) = Without

#### Electrical Characteristics:

- [Connector Impedance \(Ω\)](#) = 50
- Environmental Seal = Without

#### Body Related Features:

- Coupler Style = Quick Connect/Disconnect
- [Pin Protection](#) = Without
- Solder Lug = Without
- [Body Plating](#) = Front-Nickel/Rear-Tin

#### Contact Related Features:

- [Center Contact Plating](#) = Gold (30)
- Contacts = With

#### Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C

#### Conditions for Usage:

- [Terminate To](#) = Printed Circuit Board

#### Other:

- Brand = AMP

[Provide Website Feedback](#) | [Need Help?](#)