

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 11_MCX-50-2-19/111_N

Rev.: D



Description

Straight cable plug

Interface Standards
IEC 60169-36_CECC 22220



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 6 GHz

Mechanical Data

Centre contact soldered
Outer contact soldered
Weight 0.0006 kg

Environmental Data

Operating Temperature -65 °C to 155 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Brass
Outer contact	Copper Beryllium Alloy
Body	Brass
Insulator	PFA / PTFE

Material

Surface Plating

Hard Au min. 1.3 µm over Ni min. 1.3 µm
Hard Au min. 0.1 µm over NiP min. 2 µm
Hard Au min. 0.1 µm over NiP min. 2 µm

Related Documents

Outline drawing	DOU-00007392
Catalogue drawing	DOU-00007394
Assembly instruction	DOC-0000181794

Ordering Information

Single package	11_MCX-50-2-19/111_NE
Bulk 100 pcs package	11_MCX-50-2-19/111_NH

Additional Information

Suitable cable	EZ_86_TP_M17
----------------	--------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions