

HUBER+SUHNER® DATA SHEET

Coaxial PCB Connector: 86_CT-0-1-1/111_N

Rev.: B



Description

Right angle PCB cable terminator

Interface Standards



Technical Data

Electrical Data

Impedance other Ω
Interface frequency max. GHz

Mechanical Data

Board mounting type through holes
Weight 0.0003 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Piece Parts	Material
Centre contact	Brass
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE

Surface Plating

SUCOPRO Plating
SUCOPRO Plating
SUCOPRO Plating

Related Documents

Outline drawing	DOU-00012736
Catalogue drawing	DCA-00012738
Assembly instruction	DOC-0000192830
Mounting hole	DOU-00012739

Ordering Information

Bulk 100 pcs package	86_CT-0-1-1/111_NH
Single package	86_CT-0-1-1/111_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions

Document: DOC-0000287916 C

Issued: 11.11.04

Uncontrolled Copy

Page 1/1