

HUBER+SUHNER® DATA SHEET

Between Series Adapter: 33_PC7-TNC-50-51/11-_U

Rev.: C



Description

Adaptor plug/jack
PC 7 plug (male) / TNC-precision

Interface standards
IEEE STD 287_ANSI C 16.43



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. GHz
VSWR DC - 18 GHz
 $\leq 1.05 + 0.005 f$

Mechanical Data

Weight 0.0535 kg

Environmental Data

Operating Temperature -55 °C to 70 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts (PC 7)

Piece Parts (PC 7)	Material
Centre contact	
Outer contact	Brass
Body	Brass
Insulator	

Surface Plating

SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Piece Parts (TNC-precision)

Piece Parts (TNC-precision)	Material
Centre contact	Copper Beryllium Alloy
Outer contact	Stainless Steel
Body	Stainless Steel
Insulator	PFA / PTFE

Surface Plating

Gold Plating (without Nickel underplating)

Ordering Information

Single package 33_PC7-TNC-50-51/11-_UE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com