HUBER+SUHNER® DATA SHEET Between Series Adapter: 33_PC7-TNC-50-52/-33_N





Description

Adaptor plug/jack PC 7 plug (male) / TNC-precision jack (female)

Interface standards IEEE STD 287 ANSI C 16.43



Electrical Data

Impedance 50 Ω Interface frequency max. GHz **VSWR**

DC - 18 GHz ≤ 1.03 + 0.009 f

Mechanical Data

Number of matings 500 0.0617 kg Weight

Environmental Data

Operating Temperature -55 °C to 70 °C 2002/95/EC (RoHS) compliant

Material Data

Piece Parts (PC 7) Material

Centre contact Copper Beryllium Alloy

Outer contact Brass Body **Brass**

Insulator Air Dielectric - Bead - PPH

Coupling nut Brass Piece Parts (TNC-precision) Material

Centre contact Copper Beryllium Alloy Outer contact Stainless Steel Body Stainless Steel PFA / PTFE Insulator

Related Documents

Ordering Information

Single package 33 PC7-TNC-50-52/-33 NE

Surface Plating

SUCOPRO Plating

Gold Plating (without Nickel underplating) Gold Plating (without Nickel underplating)

SUCOPLATE (R) Plating

Surface Plating SUCOPRO Plating

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only

HUBER+SUHNER – Excellence in Connectivity Solutions

HUBER+SUHNER HUBER+SUHNER AG

RF Technology 9100 Herisau, Switzerland Phone +41 (0)71 353 41 11 +41 (0)71 353 45 90 www.hubersuhner.com

Document: DOC-0000195280 H Issued: 20.07.07 **Uncontrolled Copy** Page 1/1