

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 24\_N-50-7-15/133\_N

Rev.: D



### Description

Straight bulkhead cable feed through

Interface Standards  
IEC 61169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

Impedance 50 Ω  
Interface frequency max. 11 GHz

#### Mechanical Data

Centre contact crimped  
Outer contact crimped  
Weight 0.0389 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact  
Outer contact  
Body  
Insulator  
Fastening nut  
Washer  
Crimp ferrule

##### Material

Copper Beryllium Alloy  
Brass  
Brass  
PFA / PTFE  
Brass  
Bronze  
Brass

##### Surface Plating

Gold Plating (Nickel underplated)  
SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating  
  
SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating

#### Related Documents

Outline drawing DOU-00009122  
Catalogue drawing DCA-00008890  
Assembly instruction DOC-0000179092

#### Ordering Information

Single package 24\_N-50-7-15/133\_NE  
Bulk 100 pcs package 24\_N-50-7-15/133\_NH

#### Additional Information

Suitable cables RG\_214\_U, GX\_07272\_D, GX\_07272\_D-04

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions**



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com