

HUBER+SUHNER® DATA SHEET

Between Series Adapter: 37_N-SMC-50-1/1--_U

Rev.: D



Description

Panel adaptor jack/jack, flange mount
N jack (female) / SMC jack (female)

Interface standards
IEC 60169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	10 GHz
VSWR	DC - 10 GHz ≤ 1.06 + 0.084 f

Mechanical Data

Number of matings	500
Weight	0.0296 kg

Environmental Data

Operating Temperature	-65 °C to 165 °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts (N)

Centre contact	Material Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE

Piece Parts (SMC)

Centre contact	Material Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE

Surface Plating

Gold Plating (without Nickel underplating)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Surface Plating

Gold Plating (without Nickel underplating)
Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)

Related Documents

Outline drawing	DOU-00014069
Mounting hole	DOU-00008795

Ordering Information

Single package	37_N-SMC-50-1/1--_UE
----------------	----------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions

Document: DOC-0000195093 I

Issued: 01.09.08

Uncontrolled Copy

Page 1/1