

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 11_716-50-23-14/003_-

Rev.: C



Description

Straight cable plug

QUICK-FIT connector
For outdoor applications
Water protection according to IP 68



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	7.5 GHz
Frequency range	DC to 2.5 GHz 2.5 to 3 GHz
Return loss	≥ 30 dB ≥ 28 dB
Intermodulation	≤ -155 dBc (2 x 43 dBm carrier)

Mechanical Data

Centre contact	plugged
Outer contact	clamped
Weight	0.3331 kg

Environmental Data

Operating Temperature	-40 °C to 85 °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Bronze / Brass	Silver Plating
Outer contact	Brass	Silver Plating
Body	Brass	Silver / SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	NR (Natural Rubber)	

Related Documents

Outline drawing	DOU-00075582
Catalogue drawing	DCA-00075693
Assembly instruction	DOC-0000233737

Ordering Information

Single package	11_716-50-23-14/003_-E
----------------	------------------------

Additional Information

Suitable cables	SUCOFEED_7/8_HF, Heliax VXL5-50, Cellflex UCF78-50A
Interface standards	IEC 61169-4_CECC 22190_DIN 47223_VG 95250

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions