
Resources

My Account **Customer Support**

Home > Products > By Type > CHAMP Connectors > Product Feature Selector > Product Details

5-5175474 -7 Product Details



5-5175474

Active

1.27 [.050] Series I, HD, FH and J Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance

Product Highlights:

- Connector
- Receptacle
- Number of Positions = 60
- 1.27 mm Centerline
- Standard Profile

View all Features | Find Similar **Products**



Quick Links

Check Pricing & Availability Search for Tooling Product Feature Selector Contact Us About This Product

Documentation & Additional Information

Product Drawings:

AMP CHAMP .050 CONNECTOR (B -T-B) RECEPTACLE CONECTOR... (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

? None Available

Application Specifications:

None Available

Instruction Sheets:

? None Available

CAD Files: (CAD Format & Compression Information

- 2D Drawing (DXF, Version O)
- 3D Model_ (IGES, Version O)
- 2 3D Model (STEP, Version O)

Additional Information:

Product Line Information

Additional Product Images:

Side View

Related Products:

? Tooling

List all Documents

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Connector
- ? Gender = Receptacle
- ? Number of Positions = 60
- ? Profile = Standard
- ? PCB Mount Style = Thru Hole
- ? PCB Retention Feature = Yes
- PCB Mount Angle = Right Angle
- ? Connector Type = High Density (HD)
- ? PCB Polarization = Without
- ? Retention Leg Material = Brass
- ? Color = Black
- Used For = Board To Board Applications
- Sealed Bottom = Without

Mechanical Attachment:

? Retention Leg Plating = Tin over Nickel

Termination Related Features:

Termination (Solder) Post Length (mm [in]) 3.10 [0.122]

Body Related Features:

- Centerline (mm [in]) _ = 1.27 [0.050]
- PCB Retention Method = Boardlock(s)

Contact Related Features:

- Contact Mating Area Plating Material = Gold
- Contact Material = Phosphor Bronze

Housing Related Features:

- Proving Temperature Rating
- ? Housing Material = Nylon
- ? Housing Flammability Rating = UL 94V -0

Industry Standards:

- ? Rohs/ELV Compliance = Rohs compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Operation/Application:

? Application = Standard

Other:

? Brand = AMP

Provide Website Feedback | Contact Customer Support