

This document was generated on 11/22/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0877791001</u>		A
Status:	Active		
Overview:	micro sata		
Description:		ATA Backplane Receptacle, Through Hole, Vertical, SIL	The second second
)μ") Gold (Au) Selective, 22 Circuits, Leadfree	- Complete and
			- ANN
Documents:			A A A A A A A A A A A A A A A A A A A
3D Model		Product Specification PS-87779-011 (PDF)	and the second sec
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	- Martine
			Serie
Agency Certifica	ation		image - Reference only
CSA		LR19980	
UL		E29179	EU RoHS China RoHS
			ELV and RoHS
General			Compliant
Product Family		PCB Receptacles	REACH SVHC
Series		87779	Not Reviewed
Application		Board-to-Board, Signal	Low-Halogen Status
Overview		micro_sata	Low-Halogen
Product Literature O	rder No	SNG-029	
Product Name		Serial ATA	Need more information on product
		oona /////	environmental compliance?
Physical			Email productcompliance@molex.com
(p)ower-(s)ignal Configuration		15p - 7s	For a multiple part number RoHS Certificate
Circuits (Loaded)		22	Compliance, <u>click here</u>
Durability (mating cycles max)		500	
Flammability		94V-0	Please visit the Contact Us section for any
Glow-Wire Compliant		No	non-product compliance questions.
Lock to Mating Part		Yes	
Material - Plating Mating		Gold	
Material - Plating Termination		Tin	
Number of Rows		1	Search Parts in this Series
Orientation		Vertical	
PC Tail Length		3.45mm (.136")	<u>87779</u> Series
PCB Locator		Yes	
PCB Retention		None	Mates With
PCB Thickness - Recommended			87703 Serial ATA Combo Plug, 87799 Seri
		0.80mm (.031"), 2.50mm (.098")	ATA Combo Plug
Packaging Type		Tray)
Pitch - Mating Interfa	ace	1.27mm (.050")	
Plating min - Mating		0.762µm (30µ")	
Plating min - Termination		2.540µm (100µ")	
Polarized to Mating	Part	Yes	
Polarized to PCB		Yes	
Surface Mount Compatible (SMC)		Yes	
Temperature Range		-40°C to +105°C	
Termination Interface: Style		Surface Mount	
Electrical			
	aar Cantaat	1 5 4	
Current - Maximum Voltage - Maximum	per Contact	1.5A 30V	
0	D /		
Solder Process			
Duration at Max. Process Temperature (seconds)		10	
Lead-free Process C		SMC & Wave Capable (TH only)	
Max. Cycles at Max. Process Temperature		1	
Process Temperatur		260	

Material Info Country of Origin

HK, KR, MX, SG

Reference - Drawing Numbers Product Specification Sales Drawing

PS-87779-011 SD-87779-020

This document was generated on 11/22/2010 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION