

This document was generated on 05/11/2011

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0470804005		
Status:	Active		
Overview:	serial_ata_signal_plugs		
Description:		ATA Shrouded Signal Plug, Surface Mount, 7 Circuits, with	
Description.		or Black, 0.38µm (15µ") Gold (Au) Plating, Lead-free	
Documents:			
3D Model		Product Specification PS-67490-001 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
			Series
Agency Certification			image - Reference only
CSA		LR19980	
UL		E29179	EU RoHS China RoHS
			ELV and RoHS
General			Compliant
Product Family		PCB Headers	REACH SVHC
Series		47080	Contains SVHC: No
Application		Board-to-Board, Signal, Wire-to-Board	Low-Halogen Status
Overview		serial_ata_signal_plugs	Not Low-Halogen
Product Name		Serial ATA	Need more information on product
Physical			environmental compliance?
Breakaway		No	
Circuits (Loaded)		7	Email productcompliance@molex.com
Circuits (maximum)		7	For a multiple part number RoHS Certificate of
Durability (mating cyc	les max)	500	Compliance, <u>click here</u>
First Mate / Last Break		No	Please visit the Contact Us section for any
Flammability		94V-0	non-product compliance questions.
Glow-Wire Compliant		No	
Guide to Mating Part		No	
Keying to Mating Part		None	
Lock to Mating Part		Yes	Search Parts in this Series
Material - Plating Mating		Gold	<u>47080</u> Series
Material - Plating Termination		Tin	
Number of Rows		1	Mates With
Orientation		Right Angle	67489 Serial ATA Signal Connect. ATA
PCB Locator		Yes	Straight to Straight Signal Cable Assembly
PCB Retention			<u>887505310</u> , <u>887505318</u> , <u>887505410</u> ,
PCB Thickness - Recommended		1.60mm (.063") Embossed Tape on Reel	<u>887505418</u>
Packaging Type Pitch - Mating Interfac		1.27mm (.050")	
Plating min - Mating		0.381µm (15µ")	
Polarized to Mating Part		Yes	
Polarized to PCB		Yes	
Shrouded		No	
Stackable		No	
Temperature Range -	Operating	-35°C to +85°C	
Termination Interface	: Style	Surface Mount	
Electrical			
Current - Maximum p	er Contact	1.5A	
Voltage - Maximum		15V	
Solder Process I	Data		
Lead-free Process Ca		Reflow Capable (SMT only)	
Process Temperature		230	

Material Info

Reference - Drawing Numbers Product Specification Sales Drawing

PS-67490-001, RPS-67490-002 SD-47080-001

This document was generated on 05/11/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION