

This document was generated on 02/22/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0678007001		
Status:	Active		
Overview:	serial_ata_products	• · · · • • • • • • • • • • • • • • • •	
Description:		Serial ATA High Speed Header, Vertical, Through Hole, with	CARDA MAN
		uits, Gold (Au) Flash, for 1.60mm (.063") PCB, Black, Footprint B,	
	with PCB Locator Tab	os, Lead-free	
Documents:			
3D Model		Product Specification PS-67491-001 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	Series
			image - Reference only
	· · · ·		
Agency Certifica	tion		
CSA		LR19980	EU RoHS China RoHS
UL		E29179	ELV and RoHS
			Compliant
General			REACH SVHC
Product Family		PCB Headers	Not Reviewed
Series		<u>67800</u>	Low-Halogen Status
Application		Board-to-Board, Signal, Wire-to-Board	Not Low-Halogen
Comments		Staggered Solder Pin Footprint B	Need were information on meduat
Overview		serial ata products	Need more information on product
Product Name		Serial ATA	environmental compliance?
			Email productcompliance@molex.com
Physical Breakaway			For a multiple part number RoHS Certificate of
		No	
Circuits (Loaded)		7	Compliance, <u>click here</u>
Circuits (maximum)		7	Please visit the Contact Us section for any
Color - Resin		Black	non-product compliance questions.
			non-product compliance questions.
Durability (mating cycles max) First Mate / Last Break		50 Xaa	
	IK	Yes	
Flammability		94V-0	
Glow-Wire Compliant		No	Search Parts in this Series
Guide to Mating Part		No	<u>67800</u> Series
Keying to Mating Part		Yes	
Lock to Mating Part		Yes	
Material - Metal		Brass	
Material - Plating Mating		Gold	
Material - Plating Termination		Tin	
Number of Rows		1	
Orientation		Vertical	
PC Tail Length		2.45mm (.096")	
PCB Locator		Yes	
PCB Retention		Yes	
PCB Thickness - Rec	commended	1.60mm (.063")	
Packaging Type		Tray	
Pitch - Mating Interfac	ce	1.27mm (.050")	
Pitch - Termination In		1.27mm (.050")	
Polarized to Mating P		Yes	
Shrouded		Fully	
Stackable		No	
Surface Mount Comp	atible (SMC)	No	
Temperature Range -		-35°C to +85°C	
Termination Interface		Through Hole	
remination interface	. Style		
Electrical			
Current - Maximum p	er Contact	1.5A	

Voltage - Maximum

15V DC

Solder Process Data Lead-free Process Capability

-

Wave Capable (TH only)

Material Info

Reference - Drawing Numbers Product Specification Sales Drawing

PS-67491-001 SD-67800-007

This document was generated on 02/22/2011
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION