

This document was generated on 11/12/2010

..... INFORMATION וח

Part Number:	0716607640		_
Status:	Active		(all all all all all all all all all al
			and the second s
Overview:	ebbi_50d	50D Receptacle, Vertical, Blind-Mate, 40 Circuits	A CONTRACTOR OF
Description:	1.27Mill (.030) Filch EBBI	" SOD Receptacie, Ventical, Bind-Mate, 40 Circuits	
Documents:			
3D Model		RoHS Certificate of Compliance (PDF)	
Drawing (PDF)			
Agency Certifi	ination		Series
CSA	cation	LR19980	image - Reference only
UL		E29179	
0L		223173	EU RoHS China RoHS
General			ELV and RoHS
Product Family		PCB Receptacles	Compliant
Series		<u>71660</u>	REACH SVHC
Application		Board-to-Board, Signal	Not Reviewed
Application Tooling Part Link		622004600	Low-Halogen Status
Application Tooling	g Part Link	622005500	Not Reviewed
Overview		ebbi_50d	Need more information on product
Product Name		EBBI™	environmental compliance?
Physical			Email productcompliance@molex.com
Circuits (Loaded)		40	For a multiple part number RoHS Certificate
Color - Resin		Black	Compliance, <u>click here</u>
Durability (mating	cycles max)	2,000	Compliance, <u>click here</u>
Flammability		94V-0	Please visit the Contact Us section for any
Glow-Wire Compliant		No	non-product compliance questions.
Guide to Mating Part		Yes	
Lock to Mating Part		None	
Material - Metal		Phosphor Bronze	
Material - Plating Mating		Gold	Search Parts in this Series
Material - Plating Termination		Tin	<u>71660</u> Series
Material - Resin		High Temperature Thermoplastic	
Number of Rows		2	Mataa With
Orientation		Vertical	Mates With
PC Tail Length		3.94mm (.155")	<u>71661</u>
PCB Locator		Yes	
PCB Retention		Yes	
PCB Thickness - F	Recommended	3.94mm (.155")	
Packaging Type		Tray	
Pitch - Mating Interface		1.27mm (.050")	
Plating min - Mating		0.762µm (30µ")	
Plating min - Term		0.254µm (10µ")	
Polarized to PCB		Yes	
Surface Mount Compatible (SMC)		Yes	
Temperature Range - Operating		-40°C to +105°C	
Termination Interfa		Through Hole	
Electrical			
Current - Maximum per Contact		1A	
Voltage - Maximum		30V	
Solder Proces	s Data		
Duration at Max. Process Temperature (seconds)		40	
Lead-free Process Capability		SMC & Wave Capable (TH only)	

Lead-free Process Capability Max. Cycles at Max. Process Temperature

SMC & Wave Capable (TH only) 3

260				
MX, US				
Reference - Drawing Numbers				
PK-71660				
SDA-71660-7***				

This document was generated on 11/12/2010 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION