

## This document was generated on 01/26/2011

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0716617130</u>		
			(C)
Status:	Active		
Overview:	ebbi_50d		
Description:	1.27mm (.050") Pitch EBBI™	50D Plug, Vertical, Blind Mate, 130 Circuits, 2.79mm	The second second
	(.110") PC Tail Length		WIND I
			ALLE ALLE ALLE ALLE ALLE ALLE ALLE ALLE
Documents:			LALLAN LALAN LALAN LALAN LALAN
3D Model		Product Specification PS-71660 (PDF)	. CANTER .
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	. AMA
<u></u>			Series
Agency Certificati	on		image - Reference only
CSA	•	LR19980	
UL		E29179	EU RoHS China RoHS
02		220110	ELV and RoHS
General			Compliant
Product Family		PCB Headers	REACH SVHC
Series		71661	Not Reviewed
Application		Board-to-Board, Signal, Wire-to-Board	Low-Halogen Status
Overview		ebbi 50d	Not Reviewed
Product Name		EBBI™	
			Need more information on product environmental compliance?
Physical			environmental compliance?
Breakaway		No	Email productcompliance@molex.com
Circuits (Loaded)		130	For a multiple part number RoHS Certificate of
Circuits (maximum)		130	Compliance, <u>click here</u>
Color - Resin		Black	
Durability (mating cycle	s max)	2,000	Please visit the Contact Us section for any
First Mate / Last Break		No	non-product compliance questions.
Flammability		94V-0	
Glow-Wire Compliant		No	
Guide to Mating Part		Yes	
Keying to Mating Part		None	Search Parts in this Series
Lock to Mating Part		None	71661Series
Material - Metal		Copper Alloy	
Material - Plating Matin	g	Gold	Mates With
Material - Plating Termi	nation	Tin	EBBI™ 50D Receptacle 71660
Material - Resin		High Temperature Thermoplastic	
Number of Rows		2	
Orientation		Vertical	
PC Tail Length		2.79mm (.110")	
PCB Locator		Yes	
PCB Retention		Yes	
PCB Thickness - Recor	nmended	1.60mm (.063")	
Packaging Type		Tray	
Pitch - Mating Interface		1.27mm (.050")	
Pitch - Termination Inte		1.27mm (.050")	
Plating min - Mating		0.762µm (30µ")	
Plating min - Termination	on	1.905µm (75µ")	
Polarized to Mating Par		Yes	
Polarized to PCB		Yes	
Shrouded		Fully	
Stackable		No	
Surface Mount Compat	ible (SMC)	No	
Temperature Range - C		-40°C to +105°C	
Termination Interface: S		Through Hole	
		Through Holo	

Electrical			
Current - Maximum per Contact			
Voltage - Maximum			

1A 30V

## **Material Info**

Reference - Drawing Numbers Product Specification Sales Drawing

PS-71660 SDA-71661-7\*\*\*

## This document was generated on 01/26/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION