| | |

1-5787562-5 Product Details



1-5787562-5

TE Part Number: 1-5787562-5

Obsolete 📴

 Add to Part List Contact Product Information Center

.050 Series Cable Connectors (SCSI)

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector
- Plug
- Number of Positions = 50
- Wire/Cable Type = Ribbon Cable, Round Jacketed Cable
- Ribbon Cable Centerline Spacing = 1.27 mm

View all Features | Find Similar **Products**

Live Product Chat

Quick Links

- Check Pricing &
- Availability Search for Tooling
- Product Feature
- Selector

Additional Information:

Related Products:

Tooling

Product Line Information

Contact Us About This Product

Documentation & Additional Information

Product Drawings:

• PLUG ASSY KIT, UNASSEMBLED, AMPLIMITE .50 SERIES (PDF, English)

Catalog Pages/Data Sheets:

Product Specifications:

• Connector, AMPLIMITE, Shielded, .050 Series (PDF, English)

Application Specifications:

 AMPLIMITE .050 Series Insulation Displacement and Pr... (PDF, English)

Instruction Sheets:

- Manual Arbor Frame Assembly 58024-1 (PDF, English)
- AMP* REPAIR TOOL 58430-1 FOR AMPLIMITE* .050-SERIES ...
- AMPLIMITE .050 Series Connectors (Round-to-Flat Cable) (PDF,
- Installation and Use of Mass Termination Tooling (PDF, English)
- Cover Lacing Fixture 91293-1 for AMPLIMITE .050 Seri... (PDF,
- AMP* MANUAL MINIATURE APPLICATOR FRAME ASSEMBLY 91295-1 (PDF, English
- Cover Closing Kits and Staple Inserter Kit (PDF, English)
- Tooling Kit 768900-1 (PDF, English)

CAD Files:

· None Available

List all Documents

Product Features (Please use the Product Drawing for all design a

Product Type Features:

- <u>Product Type</u> = Connector
- Gender = Plug
- Number of Positions = 50
- Wire/Cable Type = Ribbon Cable, Round Jacketed Cable
- Wire Insulation Diameter (mm [in]) = 0.74 0.91 [0.029 0.036]
- Mating Connector Lock = Without
- Shielded = No
- Detent = Without
- Rails = Without
- <u>Termination Cover</u> = With
- Product Series = Series III
- Wire Termination Type = IDC
- Termination Cover Type = Wire Lacing
- Termination Cover Method = Unassembled
- Color = Gray
- Comment = Can be used with backshell kit when using round jacket cable

Mechanical Attachment:

Panel Attachment = Without

Termination Related Features:

Solder Tail Contact Plating = Tin over Nickel

Body Related Features:

- Ribbon Cable Centerline Spacing (mm [in]) = 1.27 [0.050]
- Wire Range (mm [AWG]) = 0.05-0.09² [30-28]

Contact Related Features:

- Contact Material = Phosphor Bronze
- Contact Mating Area Plating Material = Gold (30), Gold Flash over Palladium Nickel

- Housing Related Features:
 Housing Material = Thermoplastic
 - Housing Flammability Rating = UL 94V-0

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

Terminate To = Wire

Other:

Brand = AMP

Provide Website Feedback | Need Help?