

This document was generated on 03/03/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0744005000		
	<u>0741395068</u>		\sim
Status:	Active		
Overview:	pmc		
Description:	1.27mm (.050") Pitch EBBI [⊤] (.118") Retention Clip	^M 50D Plug, Surface Mount, Vertical, 68 Circuits, 3.00mm	
	(
Documents:			
<u>3D Model</u>		Product Specification PS-71660 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	Series
General			image - Reference only
Product Family		PCB Headers	
Series		74139	EU RoHS China RoHS
Application		Board-to-Board, Signal, Wire-to-Board	ELV and RoHS
Overview		pmc	Compliant
Product Name		EBBI™	REACH SVHC
			Not Reviewed
Physical			Low-Halogen Status
Breakaway		No	Low-Halogen
Circuits (Loaded)		68	Need more information on product
Circuits (maximum)		68	Need more information on product
Color - Resin		Black	environmental compliance?
Durability (mating cycles max)		500	Email productcompliance@molex.com
Glow-Wire Compliant		No	For a multiple part number RoHS Certificate of
Lock to Mating Part		Yes	Compliance, <u>click here</u>
Material - Metal		Brass, Phosphor Bronze	Compliance, <u>click here</u>
Material - Plating Mating		Gold	Please visit the Contact Us section for any
Material - Plating Termination		Tin	non-product compliance questions.
Material - Resin		High Temperature Thermoplastic	
Number of Rows		2	
Orientation		Vertical	
PCB Locator		Yes	Search Parts in this Series
PCB Retention		Yes	74139Series
PCB Thickness - Recommended		1.60mm (.063")	
Packaging Type		Tray	Mates With
Pitch - Mating Interface		1.27mm (.050")	<u>71660</u> , <u>87552</u>
Plating min - Mating		0.762µm (30µ")	<u>11000</u> , <u>01332</u>
Plating min - Termination		1.270µm (50µ")	
Polarized to Mating Part		Yes	
Shrouded		Fully	
Stackable		No	
Temperature Range	- Operating	-40°C to +105°C	
Termination Interfac		Through Hole	
Electrical			
Current - Maximum	per Contact	1A	
Voltage - Maximum		30V	
Solder Process	Data		
Duration at Max. Process Temperature (seconds)		40	
Lead-free Process Capability		Reflow Capable (SMT only)	
Max. Cycles at Max. Process Temperature		3	
Process Temperature max. C		260	
Material Info			

Reference - Drawing Numbers

Product Specification Sales Drawing PS-71660 SD-74139-001

This document was generated on 03/03/2011
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION