若 Tyco Electronic	20		1	Search	
Products Documentation	Cour commitment. Your advantag Resources My Account	Customer Support	,		
	IAMP Connectors > Product Feature Sele				
917738 -7 Product D					
			ſ	Live Product Chat US C	
	1.27 [.050] Series II an	d Sarias III	_	Carl S:30am - 5pm ET, Mon - F	
	Connectors				
• ( • ) • • • • • • • • • • • • • • • •	Always EU RoHS/ELV Cor	mpliant (Statemen	t of Compliance	Check Pricing & Availability	
A minimum A				Search for Tooling	
	Product Highlights:			Product Feature Selector	
5917738 -7	Mating Type = Recepta			Contact Us About	
	<ul> <li>Number of Positions =</li> <li>Terminate To Printed C</li> </ul>			This Product	
✓ <u>Active</u>	? Right Angle Mount Ang	le			
	? Yes PCB Retention Feature				
	View all Features   Products	Find Similar			
	<u>1100000</u>				
Documentation & Addition	nal Information				
Product Drawings:		Additional Information:			
2 CHAMP.050 SERIES (II) FMS -TYPE (PDF, English)		ish)		Product Line Information	
	4.5				
Catalog Pages/Data Sheets: 2 None Available			Related Prod	Related Products:	
			<u>roomig</u>	-	
Product Specifications:					
? None Available					
Application Specifications	s:				
Application Specifications ? None Available	s:				
<ul> <li>None Available</li> </ul>	s:				
<ul> <li>None Available</li> <li>Instruction Sheets:</li> </ul>	s:				
<ul> <li>None Available</li> </ul>	s:				
<ul> <li>? None Available</li> <li>Instruction Sheets:</li> <li>? None Available</li> <li>CAD Files: (CAD Formation</li> </ul>	& Compression Information	)			
<ul> <li>? None Available</li> <li>Instruction Sheets:         <ul> <li>? None Available</li> </ul> </li> <li>CAD Files: (CAD Formation 2) (DXF, Variable)</li> </ul>	& Compression Information	)			
<ul> <li>? None Available</li> <li>Instruction Sheets:</li> <li>? None Available</li> <li>CAD Files: (CAD Formation</li> </ul>	& Compression Information Version O) Persion O)	)			
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Formation 2) (DXF, None Available (DXF,</li></ul>	& Compression Information Version O) Persion O)	)			
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Formation 2) (DXF, Variable (DXF, Variable 2) (DXF,</li></ul>	& Compression Information Version O) Persion O)	) List all Documer	nts		
<ul> <li>None Available</li> <li>nstruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Formation 2) (DXF, Value)</li> <li>2D Drawing (DXF, Value)</li> <li>3D Model (IGES, Value)</li> <li>3D Model (STEP, Value)</li> </ul>	& Compression Information Version O) Persion O)	List all Documer	nts		
<ul> <li>None Available</li> <li>nstruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Formation 2) (DXF, Value 1) (DXF, Value 2) (</li></ul>	& Compression Information Version O) ersion O) ersion O)	List all Documer	nts		
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Formation 2) (CAD Files: (CAD Formation 2) (CAD Formation 2) (CAD Files: (CAD Formation 2) (CAD Files) (CAD File</li></ul>	& Compression Information Version O) ersion O) ersion O) use the Product Drawing for all design activi eptacle	ty) Contact Rel ? Conta	ated Features:	<u>g Material</u> = Selec	
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Format Arrow of the construction of the construc</li></ul>	& Compression Information Version O) ersion O) ersion O) use the Product Drawing for all design activit eptacle = 50	ty) Contact Rel ? <u>Conta</u> Gold	lated Features: ct Mating Area Platin	-	
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Format. <ul> <li>2D Drawing(DXF, N.</li></ul></li></ul>	& Compression Information Version O) ersion O) ersion O) use the Product Drawing for all design activit eptacle = 50 ht Angle	ty) Contact Rel ? <u>Conta</u> Gold	ated Features:	-	
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Format.</li> <li>2D Drawing(DXF, V</li> <li>3D Model_(IGES, Ve</li> <li>3D Model_(IGES, Ve</li> <li>3D Model_(STEP, Ve</li> <li>Product Features (Please</li> <li>Product Type Features:             <ul> <li>Mating Type = Record</li> <li>Number of Positions.</li> <li>Mount Angle = Rigf</li> <li>PCB Retention Feature</li> </ul> </li> </ul>	& Compression Information Version O) ersion O) ersion O) use the Product Drawing for all design activit eptacle = 50 nt Angle ure = Yes	ty) Contact Rel ? <u>Conta</u> Gold ? Conta Housing Re	lated Features: ct Mating Area Platin ct Material = Copper	Alloy	
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Format. <ul> <li>2D Drawing(DXF, N.</li></ul></li></ul>	& Compression Information Version O) ersion O) ersion O) use the Product Drawing for all design activit eptacle = 50 nt Angle ure = Yes ck = Without	ty) Contact Rel ? <u>Conta</u> Gold ? Conta Housing Re ? Housing	lated Features: ct Mating Area Platin ct Material = Copper lated Features: ng Material Temperat	Alloy	
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Format.</li> <li>2D Drawing(DXF, V</li> <li>3D Model_(IGES, Ve</li> <li>3D Model_(IGES, Ve</li> <li>3D Model_(STEP, Ve</li> <li>DModel_(STEP, Ve</li> </ul> Product Features (Prese Product Type Features: <ul> <li>Mating Type = Rece</li> <li>Number of Positions.</li> <li>Mount Angle = Rigf</li> <li>PCB Retention Feature</li> <li>Mating Connector Lor</li> <li>Product Series = Se</li> <li>Color = Black</li> </ul>	& Compression Information Version O) ersion O) ersion O) use the Product Drawing for all design activit eptacle = 50 nt Angle ure = Yes ck = Without eries II	ty) Contact Rel ? <u>Conta</u> Gold ? Conta Housing Re ? Housing	lated Features: ct Mating Area Platin ct Material = Copper	Alloy	
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Formation 2000)</li> <li>2D Drawing(DXF, None Available)</li> <li>2D Drawing(DXF, None Available)</li> <li>3D Model_(IGES, Vector 2000)</li> <li>3D Model_(IGES, Vector 2000)</li> <li>3D Model_(IGES, Vector 2000)</li> <li>Product Features         <ul> <li>(Please</li> </ul> </li> <li>Product Features             <ul> <li>(Please</li> </ul> </li> <li>Product Type Features:             <ul> <li>Mating Type = Record</li> <li>Number of Positions.</li> <li>Mount Angle = Right</li> <li>PCB Retention Feature</li> <li>Mating Connector Lond</li> <li>Product Series = Setemation</li> </ul> </li> </ul>	& Compression Information Version O) ersion O) ersion O) use the Product Drawing for all design activit eptacle = 50 nt Angle ure = Yes ck = Without eries II	ty) Contact Rel ? <u>Conta</u> Gold ? Conta Housing Re ? Housin ? Housin	lated Features: ct Mating Area Platin ct Material = Copper elated Features: ng Material Temperat ng Material = PBT	Alloy	
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Format. <ul> <li>2D Drawing(DXF, V</li> <li>3D Model_(IGES, Ve</li> <li>3D Model_(IGES, Ve</li> <li>3D Model_(IGES, Ve</li> <li>3D Model_(STEP, Ve</li> </ul> </li> <li>Product Features (Please</li> <li>Product Type Features:         <ul> <li>Mating Type = Reco</li> <li>Number of Positions.</li> <li>Mount Angle = Rigf</li> <li>PCB Retention Feature</li> <li>Product Series = Se</li> <li>Color = Black</li> <li>Front Shell Material =</li> </ul> </li> </ul>	& Compression Information Version O) ersion O) ersion O) use the Product Drawing for all design activit eptacle = 50 nt Angle ure = Yes ck = Without eries II	List all Documer	lated Features: ct Mating Area Platin ct Material = Copper elated Features: ng Material Temperat ng Material = PBT andards: /ELV Compliance =	Alloy	
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Format.</li> <li>2D Drawing(DXF, V</li> <li>3D Model_(IGES, Ve</li> <li>3D Model_(IGES, Ve</li> <li>3D Model_(STEP, Ve</li> <li>Product Features (Please</li> <li>Product Type Features:             <ul></ul></li></ul>	& Compression Information /ersion O) ersion O) ersion O) use the Product Drawing for all design activi eptacle = 50 nt Angle ure = Yes ck = Without eries II = Steel	ty) Contact Rel ? Conta Gold ? Conta Gold ? Conta Housing Re ? Housin ? Housin ? Housin ? Housin ? Conta Gold ? Conta Sta ? Conta Sta ? Conta Sta ? Conta ?	lated Features: ct Mating Area Platin ct Material = Copper elated Features: ng Material Temperat ng Material = PBT andards: /ELV Compliance = iant	Alloy ture = Standard = RoHS compliant, ELV	
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Format.</li> <li>2D Drawing(DXF, V</li> <li>3D Model_(IGES, Ve</li> <li>3D Model_(IGES, Ve</li> <li>3D Model_(STEP, Ve</li> <li>3D Model_(STEP, Ve</li> </ul> Product Features (Prese Product Type Features: <ul> <li>Mating Type = Rece</li> <li>Number of Positions.</li> <li>Mount Angle = Righ</li> <li>PCB Retention Feature</li> <li>Product Series = Se</li> <li>Color = Black</li> <li>Front Shell Material =</li> </ul>	& Compression Information /ersion O) ersion O) ersion O) use the Product Drawing for all design activi eptacle = 50 nt Angle tre = Yes ck = Without eries II = Steel = With	List all Documer	lated Features: ct Mating Area Platin ct Material = Copper elated Features: ng Material Temperating Material = PBT andards: /ELV Compliance = iant Free Solder Processe	Alloy ture = Standard RoHS compliant, ELV	
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Format.</li> <li>2D Drawing(DXF, V</li> <li>3D Model_(IGES, Ve</li> <li>40 Model_(IGES, Ve</li> <li>40 Mottoriang</li> <li>40 Mottoriang</li></ul>	& Compression Information /ersion O) ersion O) ersion O) use the Product Drawing for all design activi eptacle = 50 nt Angle tre = Yes ck = Without eries II = Steel = With PBT	List all Documer ty) Contact Rel ? Conta Gold ? Conta Gold ? Conta Housing Re ? Housin ? Housin ? Housin ? Housin ? Conta Gold ? Conta ? Housin ? Housin ? Lead I ? Capaba	lated Features: ct Mating Area Platin ct Material = Copper elated Features: ng Material Temperat ng Material = PBT andards: /ELV Compliance = iant	Alloy <u>ture</u> = Standard RoHS compliant, ELV <u>es</u> = Wave solder plder capable to 260°	
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Format.             <ul> <li>2D Drawing(DXF, V</li> <li>3D Model_(IGES, Ve</li> <li>Product Features</li></ul></li></ul>	& Compression Information Version O) ersion O) ersion O) use the Product Drawing for all design activi eptacle = 50 tt Angle Ire = Yes ck = Without eries II = Steel = With PBT ures:	List all Documer ty) Contact Rel ? Conta Gold ? Conta Gold ? Conta Housing Re ? Housin ? Housin ? Housin ? Housin ? Housin ? Lead I capab C, Wa ? RoHS	lated Features: ct Mating Area Platin ct Material = Copper elated Features: ng Material Temperating Material = PBT andards: /ELV Compliance = iant Free Solder Processe le to 240°C, Wave so ve solder capable to /ELV Compliance His	Alloy ture = Standard RoHS compliant, ELV s = Wave solder older capable to 260° 265°C	
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Format.             <ul> <li>2D Drawing(DXF, V</li> <li>3D Model_(IGES, Ve</li> <li>Product Features</li></ul></li></ul>	& Compression Information /ersion O) ersion O) ersion O) use the Product Drawing for all design activi eptacle = 50 nt Angle tre = Yes ck = Without eries II = Steel = With PBT	List all Documer ty) Contact Rel ? Conta Gold ? Conta Gold ? Conta Housing Re ? Housin ? Housin ? Housin ? Housin ? Housin ? Lead I capab C, Wa ? RoHS	lated Features: ct Mating Area Platin ct Material = Copper lated Features: ng Material Temperating Material = PBT andards: /ELV Compliance = iant Free Solder Processe le to 240°C, Wave so we solder capable to	Alloy ture = Standard RoHS compliant, ELV s = Wave solder older capable to 260° 265°C	
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Format.)         <ul> <li>2D Drawing(DXF, V</li> <li>3D Model_(IGES, Ve</li> <li>Mating Type_= Rect</li> <li>Number of Positions_</li> <li>Mount Angle_= Right</li> <li>PCB Retention Features</li> <li>Product Series_= Se</li> <li>Color = Black</li> <li>Front Shell Material =</li> </ul> </li> <li>Mechanical Attachment:         <ul> <li>Panel Attachment</li> <li>Tine Plate Material =</li> </ul> </li> <li>Termination (Solder)</li> </ul>	& Compression Information Version O) ersion O) ersion O) use the Product Drawing for all design activi eptacle = 50 nt Angle ure = Yes ck = Without eries II = Steel = With PBT ures: Post Length (mm [in]) =	List all Documer (y) Contact Rel ? Conta Gold ? Conta Gold ? Conta Housing Re ? Housin ? Housin ? Housin ? Housin ? Housin ? Lead I capab C, Wa ? RoHS RoHS	lated Features: ct Mating Area Platin ct Material = Copper elated Features: ng Material Temperating Material = PBT andards: /ELV Compliance = iant Free Solder Processe ive solder capable to /ELV Compliance His compliant	Alloy ture = Standard RoHS compliant, ELV s = Wave solder older capable to 260° 265°C	
<ul> <li>None Available</li> <li>Instruction Sheets: <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Format.)</li> <li>2D Drawing(DXF, V</li> <li>3D Model_(IGES, Ve</li> <li>3D Model_(IGES, Ve</li> <li>3D Model_(IGES, Ve</li> <li>3D Model_(STEP, Ve</li> </ul> <li>Product Features <ul> <li>Mating Type = Rece</li> <li>Number of Positions</li> <li>Mount Angle = Right</li> <li>PCB Retention Features</li> <li>Color = Black</li> <li>Front Shell Material =</li> </ul> </li> <li>Mechanical Attachment: <ul> <li>Panel Attachment:</li> <li>Tine Plate Material =</li> </ul> </li> <li>Termination (Solder) <ul> <li>3.10 [0.122]</li> <li>Solder Tail Contact P</li> </ul> </li>	& Compression Information Version O) ersion O) ersion O) use the Product Drawing for all design activi eptacle = 50 nt Angle ure = Yes ck = Without eries II = Steel = With PBT ures: Post Length (mm [in]) =	List all Documer (y) Contact Rel ? Conta Gold ? Conta Housing Re ? Housin ? Housin ? Housin ? Housin ? Housin ? Lead I compl ? Lead I capab C, Wa ? RoHS RoHS RoHS	lated Features: ct Mating Area Platin ct Material = Copper elated Features: ng Material Temperating Material = PBT andards: /ELV Compliance = iant Free Solder Processe ive solder capable to /ELV Compliance His compliant	Alloy ture = Standard RoHS compliant, ELV as = Wave solder older capable to 260° 265°C story = Always was	
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Formation 2000 (DXF, Value)</li> <li>2D Drawing_ (DXF, Value)</li> <li>3D Model_ (IGES, Veleta)</li> <li>3D Model_ (IGES, Veleta)</li> <li>3D Model_ (IGES, Veleta)</li> <li>3D Model_ (STEP, Veleta)</li> <li>Product Features         <ul> <li>(Prese</li> </ul> </li> <li>Product Features             <ul> <li>(Prese</li> </ul> </li> <li>Product Type Features:             <ul> <li>Mating Type_ = Record</li> <li>Number of Positions.</li> <li>Mount Angle_ = Righ</li> <li>PCB Retention Featu</li> <li>Mating Connector Lond</li> <li>Product Series_ = Set</li> <li>Color = Black</li> <li>Front Shell Material =</li> </ul> </li> <li>Mechanical Attachment:         <ul> <li>Panel Attachment</li> <li>Time Plate Material =</li> </ul> </li> <li>Termination Related Features:         <ul> <li>Termination (Solder) 3.10 [0.122]</li> <li>Solder Tail Contact P</li> </ul> </li> <li>Body Related Features:</li> </ul>	& Compression Information Version O) ersion O) use the Product Drawing for all design activit eptacle = 50 nt Angle ure = Yes ck = Without eries II = Steel = With PBT ures: Post Length (mm [in]) = Plating = Tin over Nickel	List all Documer (v) Contact Rel ? Conta Gold ? Conta Housing Re ? Housin ? Housin ? Housin ? Housin ? Housin ? Lead I capab C, Wa ? RoHS RoHS RoHS RoHS	lated Features: ct Mating Area Platin ct Material = Copper elated Features: ng Material Temperat ng Material = PBT andards: /ELV Compliance = iant Free Solder Processe le to 240°C, Wave so ve solder capable to /ELV Compliance His compliant for Usage:	Alloy ture = Standard RoHS compliant, ELV as = Wave solder older capable to 260° 265°C story = Always was	
<ul> <li>None Available</li> <li>Instruction Sheets: <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Formation 2007)</li> <li>2D Drawing(DXF, Vanage 2007)</li> <li>3D Model_(IGES, Venage 2007)</li> <li>Product Features (Please 2007)</li> <li>Product Type Features: <ul> <li>Mating Type = Record</li> <li>Number of Positions</li> <li>Mount Angle = Righ</li> <li>PCB Retention Feature</li> <li>Mating Connector Lond</li> <li>Product Series = Set</li> <li>Color = Black</li> <li>Front Shell Material =</li> </ul> </li> <li>Mechanical Attachment: <ul> <li>Panel Attachment</li> <li>Tine Plate Material =</li> </ul> </li> <li>Termination Related Feature</li> <li>Termination (Solder) 3.10 [0.122]</li> <li>Solder Tail Contact P</li> <li>Body Related Features: <ul> <li>Centerline (mm [in]) =</li> </ul> </li> </ul>	& Compression Information Version O) ersion O) ersion O) use the Product Drawing for all design activit eptacle = 50 nt Angle ure = Yes ck = Without eries II = Steel = With PBT ures: Post Length (mm [in]) = Plating = Tin over Nickel = 1.27 [0.050]	List all Documer (*) Contact Rel ? Conta Gold ? Conta Housing Re ? Housin ? Termin Other:	lated Features: ct Mating Area Platin ct Material = Copper elated Features: ng Material Temperating Material = PBT andards: /ELV Compliance = le to 240°C, Wave so ve solder capable to /ELV Compliance His compliant for Usage: nate To = Printed C	Alloy ture = Standard RoHS compliant, ELV as = Wave solder older capable to 260° 265°C story = Always was	
<ul> <li>None Available</li> <li>Instruction Sheets:         <ul> <li>None Available</li> </ul> </li> <li>CAD Files: (CAD Formation 2000 (DKF, Value)</li> <li>2D Drawing_ (DXF, Value)</li> <li>3D Model_ (IGES, Velow)</li> <li>3D Model_ (IGES, Velow)</li> <li>3D Model_ (IGES, Velow)</li> <li>3D Model_ (STEP, Velow)</li> <li>Product Features         <ul> <li>(Prese</li> </ul> </li> <li>Product Features             <ul> <li>(Prese</li> </ul> </li> <li>Product Type Features:             <ul> <li>Mating Type = Reco</li> <li>Number of Positions.</li> <li>Mount Angle = Righ</li> <li>PCB Retention Featu</li> <li>Mating Connector Lon</li> <li>Product Series = Se</li> <li>Color = Black</li> <li>Front Shell Material =</li> </ul> </li> <li>Mechanical Attachment:         <ul> <li>Panel Attachment</li> <li>Tine Plate Material =</li> </ul> </li> <li>Termination Related Features         <ul> <li>Termination (Solder) 3.10 [0.122]</li> <li>Solder Tail Contact P</li> </ul> </li> <li>Body Related Features:</li> </ul>	& Compression Information Version O) ersion O) ersion O) use the Product Drawing for all design activit eptacle = 50 nt Angle ure = Yes ck = Without eries II = Steel = With PBT ures: Post Length (mm [in]) = Plating = Tin over Nickel = 1.27 [0.050] pd = Boardlock(s)	List all Documer (v) Contact Rel ? Conta Gold ? Conta Housing Re ? Housin ? Housin ? Housin ? Housin ? Housin ? Lead I capab C, Wa ? RoHS RoHS RoHS RoHS	lated Features: ct Mating Area Platin ct Material = Copper elated Features: ng Material Temperating Material = PBT andards: /ELV Compliance = le to 240°C, Wave so ve solder capable to /ELV Compliance His compliant for Usage: nate To = Printed C	ture = Standard = RoHS compliant, ELV = Wave solder older capable to 260° 265°C story = Always was	

Provide Website Feedback Contact Customer Support

Home | Customer Support | Suppliers | Site Map. | Privacy Policy | Browser Support © 2008 Tyco Electronics Corporation All Rights Reserved