| D | |

5749925-7 Product Details

5749925-7

TE Part Number: 5749925-7

Superseded

Add to Part List Search for Replacement Parts

.050 Series Cable Connectors (SCSI)

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights: Connector Plug

- Plug
- Number of Positions = 28
 Wire/Cable Type = Ribbon Cable, Round Jacketed Cable
- Ribbon Cable Centerline Spacing = 1.27 mm

View all Features | Find Similar Products

Live Product Chat

- **Quick Links** Check Pricing &
- <u>Availability</u>
- Search for Tooling <u>Product Feature</u>
- Selector Contact Us About This Product

Additional Information: Product Line Information

Related Products:

Tooling

Documentation & Additional Information

Product Drawings:

Catalog Pages/Data Sheets:

Product Specifications:

Connector, AMPLIMITE, Shielded, .050 Series (PDF, English)

Application Specifications:

AMPLIMITE .050 Series Insulation Displacement and Pr... (PDF,

Instruction Sheets:

- Manual Arbor Frame Assembly 58024-1 (PDF, English)
- AMP* REPAIR TOOL 58430-1 FOR AMPLIMITE* .050-SERIES ... (PDF, English)
- · AMPLIMITE .050 Series Connectors (Round-to-Flat Cable) (PDF,
- Installation and Use of Mass Termination Tooling (PDF, English)
- Cover Lacing Fixture 91293-1 for AMPLIMITE .050 Seri... (PDF,
- AMP* MANUAL MINIATURE APPLICATOR FRAME ASSEMBLY 91295-1 (PDF, English)
- Cover Closing Kits and Staple Inserter Kit (PDF, English)
- Tooling Kit 768900-1 (PDF, English)

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version O)3D Model (IGES, Version O)
- 3D Model (STEP, Version O)

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- <u>Product Type</u> = Connector
- Gender = Plug
- Number of Positions = 28
- Wire/Cable Type = Ribbon Cable, Round Jacketed Cable
- <u>Wire Insulation Diameter (mm [in])</u> = 0.74 0.91 [0.029 0.036]
- Mating Connector Lock = Without
- Shielded = No
- Detent = Without
- Rails = Without
- Termination Cover = With
- Product Series = Series III
- Wire Termination Type = IDC
- Termination Cover Type = Standard
- Termination Cover Method = Assembled
- Color = Black
- Comment = Can be used with backshell kit when using round jacket cable

Mechanical Attachment:

<u>Panel Attachment</u> = Without

Termination Related Features:

Solder Tail Contact Plating = Tin over Nickel

Body Related Features:

- Ribbon Cable Centerline Spacing (mm [in]) = 1.27 [0.050]
- Wire Range (mm [AWG]) = 0.05-0.09² [30-28]

Contact Related Features:

- Contact Material = Phosphor Bronze
- Contact Mating Area Plating Material = Gold (30), Gold Flash over Palladium Nickel

Housing Related Features:

- Housing Material = Thermoplastic
- Housing Flammability Rating = UL 94V-0

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

Terminate To = Wire

Brand = AMP

Provide Website Feedback | Need Help?