

440027-3 Product Details



440027-3

[Pending Obsolescence Search for Replacement Parts](#)

2.16 [.085] Printed Circuit Board Connectors

[5 of 6 EU RoHS/ELV Compliant \(Find RoHS Compliant Alternates/Statement of Compliance\)](#)

Product Highlights:

- Receptacle
- Number of Positions = 36
- PCB Mount Style = Right Angle
- Standard Orientation
- Standard Profile

[View all Features](#) | [Find Similar Products](#)

Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri

Quick Links

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • RCPT. ASS'Y, 36P RIGHT ANGLE, CENTRONICS. (PDF, English) <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling
List all Documents	

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Gender = Receptacle • Number of Positions = 36 • PCB Mount Style = Right Angle • Orientation = Standard • Profile = Standard • Shielded = Yes • Mating Connector Lock = With • Mating Connector Lock Type = Bail Lock • PCB Retention Feature = Yes • Grounded = No • PCB Thickness (mm [in]) = 1.60 - 3.20 [0.063 - 0.125] • Panel Thickness (mm [in]) = 1.60 [0.063] • Color = Black • Shield Material = Steel • Comment = Spring latch fastener: Rivet (M3) <p>Mechanical Attachment:</p> <ul style="list-style-type: none"> • Panel Attachment = With • Panel Attachment Style = Rear Mount • Bail-Clip Material = Stainless Steel 	<p>Body Related Features:</p> <ul style="list-style-type: none"> • PCB Retention Method = Boardlock(s) • Shield Plating = Nickel <p>Contact Related Features:</p> <ul style="list-style-type: none"> • Contact Mating Area Plating = Gold Flash • Contact Material = Copper Alloy <p>Housing Related Features:</p> <ul style="list-style-type: none"> • Housing Material = Thermoplastic Glass Reinforced • Housing Flammability Rating = UL 94V-0 <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = ELV compliant, 5 of 6 Compliant • Lead Free Solder Processes = Wave solder capable to 240°C <p>Packaging Related Features:</p> <ul style="list-style-type: none"> • Packaging Quantity = 150 <p>Other:</p> <ul style="list-style-type: none"> • Brand = AMP