


5917334 -7 Product Details

Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



5917334 -7

Active

1.27 [.050] Series II and Series III Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- ? Mating Type = Receptacle
- ? Number of Positions = 50
- ? Terminate To Printed Circuit Board
- ? Vertical Mount Angle
- ? Yes PCB Retention Feature

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> ? REC HEADER ASSY VERTICAL W/RETENTION LEG CHAMP .050 ... (PDF, English) <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> ? None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> ? None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> ? None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> ? None Available <p>CAD Files: (CAD Format & Compression Information)</p> <ul style="list-style-type: none"> ? 2D Drawing (DXF, Version O) ? 3D Model (IGES, Version O) ? 3D Model (STEP, Version O) <p style="text-align: right;">List all Documents</p>	<p>Additional Information:</p> <ul style="list-style-type: none"> ? Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> ? Tooling

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> ? Mating Type = Receptacle ? Number of Positions = 50 ? Mount Angle = Vertical ? PCB Retention Feature = Yes ? Mating Connector Lock = Without ? Product Series = Series II ? PCB Thickness (mm [in]) = 1.60 [0.063] ? Panel Thickness (mm [in]) = 2.01 [0.079] ? Color = Black ? Shell Material = Steel <p>Mechanical Attachment:</p> <ul style="list-style-type: none"> ? Panel Attachment = With <p>Termination Related Features:</p> <ul style="list-style-type: none"> ? Termination (Solder) Post Length (mm [in]) = 3.10 [0.122] ? Solder Tail Contact Plating = Tin over Nickel <p>Body Related Features:</p> <ul style="list-style-type: none"> ? Centerline (mm [in]) = 1.27 [0.050] ? PCB Retention Method = Boardlock(s) ? Shell Plating = Nickel 	<p>Contact Related Features:</p> <ul style="list-style-type: none"> ? Contact Mating Area Plating = Gold (12) ? Contact Material = Phosphor Bronze <p>Housing Related Features:</p> <ul style="list-style-type: none"> ? Housing Material Temperature = Standard ? Housing Material = Thermoplastic, Zinc Diecast ? Housing Flammability Rating = UL 94V -0 <p>Industry Standards:</p> <ul style="list-style-type: none"> ? RoHS/ELV Compliance = RoHS compliant, ELV compliant ? Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C ? RoHS/ELV Compliance History = Always was RoHS compliant <p>Conditions for Usage:</p> <ul style="list-style-type: none"> ? Terminate To = Printed Circuit Board <p>Other:</p> <ul style="list-style-type: none"> ? Brand = AMP