

This document was generated on 02/23/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	007000000		
	<u>0679260002</u>		
Status: Active			1 Pagar
Overview: <u>serial_ata_power_connecto</u>			
		erial ATA IDT Power Receptacle, 0.76mm (30m") Gold (Au)	/ // 75%
	Plating, 18AWG, with La	atch, without Bump, Lead free	$ \mathbf{b} \mathbf{k} \mathbf{k} \mathbf{k} \mathbf{k} \mathbf{k} \mathbf{k} \mathbf{k} k$
Documents:			
<u>3D Model</u>		RoHS Certificate of Compliance (PDF)	
Drawing (PDF)			Series
			image - Reference only
General			
Product Family		IDT and Solder Connectors	
Series		<u>67926</u>	EU RoHS China RoHS ELV and RoHS
Crimp Quality Equipment		Yes	
Overview		serial ata_power_connector	Compliant REACH SVHC
Product Name		Serial ATA	Not Reviewed
Use With		<u>67926-0040</u> Feed-to Cover, <u>67926-0041</u> Feed-Through Cover	Low-Halogen Status
		COVEI	Not Low-Halogen
Physical			_
Circuits (Loaded)		5	Need more information on product
Color - Resin		Black	environmental compliance?
Durability (mating cycles max)		50	Email productcompliance@molex.com
Gender	,	Female	For a multiple part number RoHS Certificate of
Glow-Wire Compliant		No	Compliance, click here
Lock to Mating Part		Yes	
Material - Metal		Copper Alloy	Please visit the <u>Contact Us</u> section for any
Material - Plating Mating		Gold	non-product compliance questions.
Material - Plating Termination		Tin	
Number of Rows		1	
Packaging Type		Tray	
Panel Mount		No 3.84mm (150")	Search Parts in this Series
Pitch - Mating Interface Pitch - Termination Interface		3.81mm (.150") 3.81mm (.150")	<u>67926</u> Series
Plating min - Mating		0.762µm (30µ")	
Plating min - Termination		1.905µm (75µ")	Mates With
Polarized to Mating Part		Yes	87679
Temperature Range - Operating		-35°C to +85°C	
Wire Size AWG	- ,	18	Application Tooling FAQ
			Tooling specifications and manuals are
Electrical			found by selecting the products below.
Current - Maximum p	er Contact	1.5A	Crimp Height Specifications are then
Voltage - Maximum		15V DC	contained in the Application Tooling Specification document.
Calder Drasses Data			Global
Solder Process Data		000	Description Product #
Process Temperature	e max. C	230	Insertion Tool for 0638133503
Material Info			3.96mm (.156") Pitch
material into			KK® IDT Crimp
Reference - Drawing Numbers			Terminals
Sales Drawing		SD-67926-001	

This document was generated on 02/23/2011
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION