

This document was generated on 05/02/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status:	<u>0470182001</u>		MD.
Overview: serial ata 127 host re Description: 1.27mm (.050") Pitch S		n Serial ATA Host Receptacle, Mating Height 4.30mm (.169"), (Au) Plating, Light Tin Solder Area, Surface Mount, Right Angle,	
Documents: <u>3D Model</u> Drawing (PDF)		Product Specification PS-67492-001 (PDF) RoHS Certificate of Compliance (PDF)	Ser
Agency Certifica	ation		image - Reference only
CSA		LR19980	EU RoHS China RoHS
UL		E29179	ELV and RoHS
		223113	Compliant
General			REACH SVHC
Product Family		PCB Receptacles	Not Reviewed
Series		47018	Low-Halogen Status
Application		Board-to-Board, Signal	Not Low-Halogen
Comments		Top Mount Type	Need more information on product
Overview		serial_ata_127_host_receptacles	environmental compliance?
Product Name		Serial ATA	
Deviced		Email productcompliance@molex.com	
Physical			For a multiple part number RoHS Certificat
Circuits (Loaded)		22	Compliance, <u>click here</u>
Color - Resin		Black	Diagon visit the Contact Lie continue for any
Durability (mating cycles max)		500	Please visit the <u>Contact Us</u> section for any non-product compliance questions.
Flammability		94V-0	non-product compliance questions.
Glow-Wire Compliant		No	
Keying to Mating Part		Yes	
Lock to Mating Part		None	
Material - Metal		Copper Alloy	Search Parts in this Series
Material - Plating Mating		Gold	47018Series
Material - Plating Termination		Tin	
Number of Rows Orientation		1 Dight Anglo	Mates With
PC Tail Length		Right Angle 1.60mm (.063")	<u>87703-0001</u>
PCB Locator		Yes	
PCB Retention		Yes	
Packaging Type		Tray	
Pitch - Mating Interface		1.27mm (.050")	
Pitch - Termination Interface		1.27mm (.050")	
Plating min - Mating		0.762µm (30µ")	
Plating min - Termination		2.032µm (80µ")	
Polarized to Mating Part		Yes	
Polarized to PCB		Yes	
Surface Mount Compatible (SMC)		N/A	
Temperature Range - Operating		-35°C to +85°C	
Termination Interface	e: Style	Surface Mount	
Electrical			
Current - Maximum per Contact		1.5A	
Voltage - Maximum		15V DC	
Solder Process	Data		
Lead-free Process C		Reflow Capable (SMT only)	
Process Temperature max. C		230	

Material Info

Reference - Drawing Numbers Product Specification Sales Drawing

PS-67492-001 SD-47018-001

This document was generated on 05/02/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION