

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0783200002](#)
Status: **Active**
Overview: [micro_sata](#)
Description: 1.27mm (.050") Pitch High Speed Micro Serial ATA Device Receptacle for 1.8" HDD/SSD, SMT, Right Angle, Top Mount, with Support Rib, Tape on Reel, Lead free

Documents:

[3D Model](#) [Product Specification PS-78320-002 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA LR19980
 UL E29179

General


Product Family PCB Receptacles
 Series [78320](#)
 Application Board-to-Board, Signal
 Comments With Optional Manufacturing Pins (S1 to S7 and P1 to P9)
With Central Support Rib on Underside of Housing
 Overview [micro_sata](#)
 Product Name Micro Serial ATA, Serial ATA

Physical

Circuits (Loaded) 16
 Circuits (maximum) 16
 Color - Resin Black
 Durability (mating cycles max) 500
 Flammability 94V-0
 Glow-Wire Compliant No
 Guide to Mating Part Yes
 Keying to Mating Part Yes
 Lock to Mating Part Yes
 Material - Metal Copper Alloy
 Material - Plating Mating Gold
 Material - Plating Termination Tin
 Material - Resin Nylon
 Number of Rows 1
 Orientation Right Angle
 PCB Locator Yes
 PCB Retention Yes
 Packaging Type Embossed Tape on Reel
 Pitch - Mating Interface 1.27mm (.050"), 5.08mm (.200")
 Pitch - Termination Interface 1.27mm (.050"), 5.08mm (.200")
 Plating min - Mating 0.762µm (30µ")
 Plating min - Termination 2.540µm (100µ")
 Polarized to Mating Part Yes
 Polarized to PCB Yes
 Stackable No
 Temperature Range - Operating -40°C to +105°C
 Termination Interface: Style Surface Mount

Electrical

Current - Maximum per Contact 1.5A
 Grounding to PCB Yes



<p>EU RoHS ELV and RoHS Compliant REACH SVHC Contains SVHC: No Low-Halogen Status Not Low-Halogen</p>	<p>China RoHS</p>
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------

Need more information on product environmental compliance?

Email productcompliance@molex.com
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[78320Series](#)

Mates With
[78103](#) , [78283](#) and [78285](#) Micro SATA Device Plugs

Voltage - Maximum 30V

Solder Process Data

Duration at Max. Process Temperature (seconds)	10
Lead-free Process Capability	Reflow Capable (SMT only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	260

Material Info

Reference - Drawing Numbers

Product Specification	PS-78320-002
Sales Drawing	SD-78320-002

This document was generated on 01/24/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION