


# EC2EE

S E R I E S

## 15 WATT DC-DC CONVERTERS



### Features

- 15W Isolated Output
- Six-Sided Shield Metal Case
- Regulated Outputs
- Efficiency to 84%
- Fixed 200KHz Switching Frequency
- Remote On/Off Control

MODEL NUMBER	INPUT VOLTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT	INPUT CURRENT		% EFF.	SIZE
				NO LOAD	FULL LOAD		
EC2EE01	9-18 VDC	5 VDC	3000 mA	20 mA	1700 mA	77	2.56" x 3"
EC2EE02		12 VDC	1250 mA	20 mA	1600 mA	78	
EC2EE03		15 VDC	1000 mA	20 mA	1600 mA	78	
EC2EE04		±12 VDC	±625 mA	35 mA	1520 mA	82	
EC2EE05		±15 VDC	±500 mA	35 mA	1520 mA	82	
EC2EE06		5/±12 VDC	1500/±310 mA	30 mA	1600 mA	78	
EC2EE07		5/±15 VDC	1500/±250 mA	30 mA	1600 mA	78	
EC2EE08		+5/+12/-5 VDC	1500/310/500 mA	30 mA	1470 mA	78	
EC2EE11	18-36 VDC	5 VDC	3000 mA	25 mA	810 mA	77	2.56" x 3"
EC2EE12		12 VDC	1250 mA	25 mA	780 mA	80	
EC2EE13		15 VDC	1000 mA	25 mA	780 mA	80	
EC2EE14		±12 VDC	±625 mA	25 mA	750 mA	84	
EC2EE15		±15 VDC	±500 mA	25 mA	750 mA	84	
EC2EE16		5/±12 VDC	1500/±310 mA	25 mA	780 mA	80	
EC2EE17		5/±15 VDC	1500/±250 mA	25 mA	780 mA	80	
EC2EE18		+5/+12/-5 VDC	1500/310/500 mA	25 mA	715 mA	80	
EC2EE21	36-72 VDC	5 VDC	3000 mA	10 mA	410 mA	77	2.56" x 3"
EC2EE22		12 VDC	1250 mA	10 mA	390 mA	80	
EC2EE23		15 VDC	1000 mA	10 mA	390 mA	80	
EC2EE24		±12 VDC	±625 mA	15 mA	380 mA	82	
EC2EE25		±15 VDC	±500 mA	15 mA	380 mA	82	
EC2EE26		5/±12 VDC	1500/±310 mA	15 mA	380 mA	82	
EC2EE27		5/±15 VDC	1500/±250 mA	15 mA	380 mA	82	
EC2EE28		+5/+12/-5 VDC	1500/310/500 mA	15 mA	350 mA	82	

NOTE: 1. Nominal Input Voltage 12, 24 or 48 VDC

### Specifications

**INPUT SPECIFICATIONS:**

Input Voltage Range:	12V.....9-18V
24V.....18-36V	
48V.....36-72V	
Input Filter:	PI Type

**OUTPUT SPECIFICATIONS:**


Voltage Accuracy	±1.0% max.
Single Output	±1.0% max.
Dual +Output	±3.0% max.
-Output	±2.0% max.
Triple, 5V	±3.0% max.
12V/15V	±3.0% max.
Voltage Balance (Dual)	±1.0% max.
Transient Response:	
Single, 25% Step Load Change	<500µ sec.
Dual-FL-1/2L ±1% Error Band	<500µ sec.
External Trim Adj. Range	±10%.
Ripple & Noise, 20MHz BW	10mV RMS, max.
Temperature Coefficient	75mV p-p max.
Short Circuit Protection	Continuous
Line Regulation, Single/Dual	±0.2% max.
Triple	±1.0% max.
Load Regulation, Single/Dual	±1.0% max.
Triple	±5.0% max.

**GENERAL SPECIFICATIONS:**

Efficiency	See Table
Isolation Voltage	500 VDC min.
Isolation Resistance	>10ohms
Switching Frequency	200kHz, typ.
Operating Ambient Temperature Range	-25°C to +71°C
De-rating, Above 71°C	Linearly to Zero power at 100°C
Case Temperature	100°C max
Cooling	Natural Convection
Storage Temperature Range	-55°C to +100°C
EMV/RFI	Six-Sided Continuous Shield
Dimensions	2.56 x 3.00 x 0.83 inches
Case Material	Black Coated Copper with Non-Conductive Base
Weight	173g

**NOTE:**


1. Measured From High Line to Low Line
2. Measured From Full Load to 1/4 Load
3. Maximum case temperature under any operating condition should not be exceeded 100°C.



All Specifications Typical At Nominal Line, Full Load and 25°C Unless Otherwise Noted.

### Remote On/Off Control

Logic Compatibility	CMOS or Open Collector TTL
EC-On	±3.5 VDC or Open Circuit
EC-Off	<1.8 VDC
Shutdown Idle Current	10mA
Control Common	Referenced to Input Minus



### PIN CONNECTION

Pin	Single Output	Dual Output	Triple Output
1	+Input	+Input	+Input
2	-Input	-Input	-Input
3	No Pin	+Output	+Output
4	Output Trim	Common	Common
5	No Pin	-Output	-Output
6	+Output	No Pin	+5V Output
7	-Output	No Pin	No Pin
8	Remote On/Off Control		

### TRIPLE OUTPUT LOADING TABLE (1)

Output (Pin No.)	Voltage	Amperes	
		Min. (2)	Nom.
6	+5	0.25	1.5
3 & 5	+12 & -12	0.10	0.31
3 & 5	+15 & -15	0.10	0.25
3 & 5	+12 & -5	0.10 / 0.10	0.31 / 0.50

**NOTE:**

1. Maximum total power from all outputs is limited to 15 watts but no output should exceed its maximum current.
2. Minimum current on each output is required to maintain specified regulation.

