

Inductors Commercial, Molded



FEATURES

- Inductance range is 1 μ H to 2200 μ H
- Proven reliability molded inductors



**RoHS
COMPLIANT**

STANDARD ELECTRICAL SPECIFICATIONS

MODEL*	IND. (μ H)	TOL.	Q MIN.	TEST FREQ. (MHz)	SRF MIN. (MHz)	DCR MAX. (Ohms)	RATED* DC CURRENT (mA)
IM-10RFCM-13	1.0	$\pm 10\%$	100	15	136	0.04	2700
IM-10RFCM-13	1.2	$\pm 10\%$	100	15	124	0.04	2700
IM-10RFCM-13	1.5	$\pm 10\%$	100	10	112	0.04	2700
IM-10RFCM-13	1.8	$\pm 10\%$	95	10	100	0.05	2500
IM-10RFCM-13	2.2	$\pm 10\%$	95	10	88	0.05	2500
IM-10RFCM-13	2.7	$\pm 10\%$	68	7.9	76	0.05	2500
IM-10RFCM-13	3.3	$\pm 10\%$	60	7.9	72	0.05	2500
IM-10RFCM-13	3.9	$\pm 10\%$	60	7.9	70	0.07	2100
IM-10RFCM-13	4.7	$\pm 10\%$	60	7.9	60	0.09	1800
IM-10RFCM-13	5.6	$\pm 10\%$	65	7.9	56	0.14	1550
IM-10RFCM-13	6.8	$\pm 10\%$	70	7.9	52	0.17	1300
IM-10RFCM-13	8.2	$\pm 10\%$	65	7.9	46	0.25	1150
IM-10RFCM-13	10	$\pm 10\%$	65	5	40	0.32	1000
IM-10RFCM-13	12	$\pm 10\%$	65	5	36	0.47	870
IM-10RFCM-13	15	$\pm 10\%$	75	4	32	0.62	730
IM-10RFCM-13	18	$\pm 10\%$	65	4	30	0.72	660
IM-10RFCM-13	22	$\pm 10\%$	65	2.5	28	0.80	600
IM-10RFCM-13	27	$\pm 5\%$	65	2.5	25	1.2	520
IM-10RFCM-13	33	$\pm 5\%$	80	2.5	22	1.5	450
IM-10RFCM-13	39	$\pm 5\%$	80	2.5	20	2.3	380
IM-10RFCM-13	47	$\pm 5\%$	100	2.5	19	3.0	300
IM-10RFCM-13	56	$\pm 5\%$	100	2.5	18	4.2	270
IM-10RFCM-13	68	$\pm 5\%$	100	2.5	16	5.2	250
IM-10RFCM-13	82	$\pm 5\%$	100	2.5	14	6.2	220
IM-10RFCM-13	100	$\pm 5\%$	100	1.5	13	7.0	200
IM-10RFCM-13	120	$\pm 5\%$	95	1.5	11	7.5	200
IM-10RFCM-13	150	$\pm 5\%$	90	1	9	8	190
IM-10RFCM-13	180	$\pm 5\%$	85	1	7	9	185
IM-10RFCM-13	220	$\pm 5\%$	85	1	5.5	10	180
IM-10RFCM-13	270	$\pm 5\%$	80	1	4.5	11	172
IM-10RFCM-13	330	$\pm 5\%$	80	0.80	3.5	12	165
IM-10RFCM-13	390	$\pm 5\%$	75	0.80	3.0	13	157
IM-10RFCM-13	470	$\pm 5\%$	75	0.80	2.8	14	150
IM-10RFCM-13	560	$\pm 5\%$	65	0.80	2.5	16	145
IM-10RFCM-13	680	$\pm 5\%$	65	0.80	2.2	17	140
IM-10RFCM-13	820	$\pm 5\%$	65	0.80	2.0	19	132
IM-10RFCM-13	1000	$\pm 5\%$	70	0.50	1.8	21	125
IM-10RFCM-13	1200	$\pm 5\%$	60	0.25	2.2	22	120
IM-10RFCM-13	2200	$\pm 5\%$	70	0.25	1.6	30	100

IRON CORE

*Model electricals and tolerances shown.

ELECTRICAL SPECIFICATIONS

Inductance Tolerance: $\pm 10\%$ on Q-Meter for 1 μ H to 22 μ H.
 $\pm 5\%$ 1000 cps bridge for 27 μ H to 2200 μ H.

NOTE: L and Q are not always tested at the same frequency. Inductance values tested on Q-Meter, are tested at standard test frequencies.

Dielectric Strength: 700 VRMS at sea level

Operating Temperature: - 55 $^{\circ}$ C to + 125 $^{\circ}$ C

Self-Resonant Frequency: Minimum SRF measured with full length leads on Grid-Dip Meter

Q: Measured on Q-Meter

Rating: 1/3 watt dissipation for M Models

MECHANICAL SPECIFICATIONS

Terminal Strength: Meets 5 pound pull test when tested per MIL-PRF-15305

DENSITY SPECIFICATIONS

Weight: 2 grams maximum


ENVIRONMENTAL SPECIFICATIONS

Moisture: Meets requirements of MIL-PRF-15305.

Shock Resistance: Meets requirements of MIL-PRF-15305.

Vibration: High frequency, 10 Hz to 2000 Hz at 20 G $\pm 10\%$ maximum for 12 logarithmic swings, each of 20 minute duration repeated for each of three mutually perpendicular planes.

DIMENSIONS in inches [millimeters]



MARKING

— Color coded

ORDERING INFORMATION

IM-10RFCM-13	1.0 μ H	10 %	EZ	e2
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER

I	M	1	0	R	F	C	M	E	Z	1	R	0	K	1	3
MODEL							PACKAGE CODE	INDUCTANCE VALUE			INDUCTANCE TOLERANCE		SERIES		



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.