



List Price \$166.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.****Technical Characteristics**

Head Type	Top Plunger
Actuator	Reinforced Steel Roller Plunger (ZCKE67)
Rated Thermal Current	10A
Approvals	UL Listed - CSA Certified - CE Marked
Conforming to Standards	CENELEC EN 50041
RoHS	Yes
Body Type	Standard
Body Material	Metal
Connection Type	Conduit Entrance (0.5" NPT)
Contact Block	XE2SP2151
Terminal Type	Screw Clamp
Shock Resistance	50g
Vibration Resistance	25g (10-500Hz)
Weight	1.0 lbs (0.455 kg)
Contact Configuration	1 N.O./1 N.C.
Contact Operation	Snap Action
Positive Opening	Yes
Actuation	Horizontal
Maximum Actuation Speed	1 m/s
Actuator Action	Momentary
Lever Arm Length	n/a
Roller Dimension	0.63" x 0.12" (16 x 3mm)
Operating Torque/Force	48 Inch-Ounces (0.33Nm)
Marketing Trade Name	OsiSense
Maximum Voltage Rating	240VAC/250VDC
NEMA Enclosure Rating	NEMA 1/2/4/12
Operating Temperature Range	-13 to 158°F (-25 to 70°C)
Type	XCKJ
Type of Duty	Heavy Duty
Degree of Protection	IP 66

**Shipping and Ordering**

Category	22411 - Limit Switches, Heavy Duty, IEC, Type XCKJ
----------	--

Generated: 08/10/2011 19:48:52

Discount Schedule	T
GTIN	00785901093749
Package Quantity	1
Weight	1.06 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y
Country of Origin	ID

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.