

List Price \$243.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.****Technical Characteristics**

| | |
|-----------------------------|-----------------------------------------------------------------------------------------------------|
| Contact Configuration | 1 N.O./1 N.C. |
| Contact Operation | Snap Action |
| Contact Form | Form Z - SPDT-DB |
| Terminal Type | Screw Clamp |
| Ampere Rating | 15A |
| Maximum Voltage Rating | 600V |
| Enclosure Rating | Open |
| Head Type | Rotary |
| Operating Temperature Range | -65 to 185 Degrees F |
| Type | AW |
| Type of Duty | Heavy Duty |
| Actuation | CCW |
| Actuator Action | Momentary |
| Actuator | Lever Arm (ordered separately) |
| Operating Torque/Force | 2.75 Inch-Pounds |
| Total Travel | 30 Degrees |
| Differential Travel | 2.5 Degrees |
| Pre-Travel | 5 Degrees |
| Approvals | UL Listed File Number E42259 CCN NKCR - CSA Certified File Number LR25490 Class 3211-03 - CE Marked |
| Body Material | Cast Zinc |
| Connection Type | Conduit Entrance (0.5 Inch NPT) |

Shipping and Ordering

| | |
|-------------------|-------------------------------------------------------------------------|
| Category | 21495 - Limit Switches, Open, Type AO12 thru AO56 |
| Discount Schedule | DS1 |
| GTIN | 00785901807605 |
| Package Quantity | 10 |
| Weight | 0.59 lbs. |
| Availability Code | Stock Item: This item is normally stocked in our distribution facility. |
| Returnability | Y |
| Country of Origin | MX |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.