

List Price \$291.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.****Technical Characteristics**

Contact Configuration	1 N.O./1 N.C.
Contact Operation	Snap Action
Contact Form	Form Z - SPDT-DB
Terminal Type	Screw Clamp
Ampere Rating	15A
Maximum Voltage Rating	600V
Enclosure Rating	Open
Head Type	Top Plunger
Operating Temperature Range	0 to 185 Degrees F
Type	AW
Type of Duty	Heavy Duty
Actuation	Horizontal
Actuator Action	Momentary
Actuator	Roller
Roller Dimension	0.63 x 0.25 Inches
Roller Material	Sintered Iron (Oil-Impregnated)
Operating Torque/Force	3.00 Inch-Pounds
Total Travel	0.19 to 0.31 Inches
Differential Travel	0.05 Inches
Pre-Travel	0.09 Inches
Approvals	UL Listed File Number E42259 CCN NKCR - CSA Certified File Number LR25490 Class 3211-03 - CE Marked
Body Material	Cast Zinc
Connection Type	Conduit Entrance (0.5 Inch NPT)

Shipping and Ordering

Category	21495 - Limit Switches, Open, Type AO12 thru AO56
Discount Schedule	DS1
GTIN	00785901817239
Package Quantity	1
Weight	0.59 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y
Country of Origin	MX

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 08/10/2011 19:52:00