



List Price \$248.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.**

Technical Characteristics

Operating Torque/Force	3 Pounds
Basic Switch (Plug-In Unit)	Compact
Actuator	Top Roller-Plunger
Actuation	Horizontal
Turret Head	Top Plunger
Plug-In Receptacle	Compact
Actuator Action	Spring Return
Total Travel	0.25 Inches
Differential Travel	0.02 Inches
Approvals	UL Listed - CSA Certified - CE Marked
Pre-Travel	0.08 Inches
Body Material	Zinc Alloy
Connection Type	0.5 Inch NPT Conduit Entrance (screw clamp terminals)
Contact Operation	Snap Action
Contact Rating	NEMA A600/Q600
Contact Material	Silver Alloy
Contact Configuration	1 NO/1 NC
Ampere Rating	10A
Contact Form	Form Z - SPDT-DB
Maximum Voltage Rating	600V
Pilot Light	None
Operating Temperature Range	0°F to 185°F
Type of Duty	Heavy Duty
Type	C

Shipping and Ordering

Category	21499 - Limit Switches, Heavy Duty, Type C
Discount Schedule	DS1
GTIN	00785901783374
Package Quantity	1
Weight	0.93 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y

Generated: 08/10/2011 19:52:03

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.