



List Price \$120.00 USD

Availability **Non-Stock Item: This item is not normally stocked in our distribution facility.****Technical Characteristics**

Contact Configuration	1 N.O./1 N.C.
Contact Operation	Snap Action
Positive Opening	Yes
Terminal Type	Screw Clamp
Ampere Rating	10A
Maximum Voltage Rating	240VAC/250VDC
NEMA Enclosure Rating	NEMA 1/2/4/6/6P/12/13
Degree of Protection	IP66
Operating Temperature Range	-13 to 158°F (-25 to 70°C)
Type	XCKL
Type of Duty	General Duty
Shock Resistance	50G
Vibration Resistance	25G
Weight	0.573 lbs (0.260kg)
Actuator	Steel Roller Plunger (ZCKD02)
Head Type	Top Plunger
Actuation	Horizontal
Actuator Action	Momentary
Maximum Actuation Speed	0.5 m/s
Repeat Accuracy	0.05mm (on the tripping points)
Lever Arm Length	n/a
Roller Dimension	12mm x 4.0mm
Operating Torque/Force	35.6 Inch-Ounces (0.25Nm)
Marketing Trade Name	OsiSense
Approvals	UL Listed - CSA Certified - CE Marked
Conforming to Standards	IEC and EN 60204-1 EN
RoHS	No
Body Type	Compact (ZCKL1)
Body Material	Metal (Zamak)
Connection Type	Conduit Entrance (0.5" NPT)

Shipping and Ordering

Category	22416 - Limit Switches, General Duty, Compact, IEC, Type XCKL
----------	---

Generated: 08/10/2011 19:54:12

Discount Schedule	T
GTIN	00785901646488
Package Quantity	1
Weight	0.57 lbs.
Availability Code	Non-Stock Item: This item is not normally stocked in our distribution facility.
Returnability	N
Country of Origin	FR

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 08/10/2011 19:54:12