



NUMBER OF CIRCUITS	"A" DIM.	"B" DIM.	"C" DIM.	MATERIAL NUMBER
01	5.46 [215]	N/A	N/A	391000801
02	13.46 [530]	8.00 [315]	N/A	391000802
03	21.46 [845]	16.00 [630]	8.00 [315]	391000803
04	29.46 [1160]	24.00 [945]	16.00 [630]	391000804
05	37.47 [1475]	32.00 [1260]	24.00 [945]	391000805
06	45.47 [1790]	40.01 [1575]	32.00 [1260]	391000806
07	53.47 [2105]	48.01 [1890]	40.00 [1575]	391000807
08	61.47 [2420]	56.01 [2205]	48.00 [1890]	391000808
09	69.47 [2735]	64.01 [2520]	56.00 [2205]	391000809
10	77.47 [3050]	72.01 [2835]	64.00 [2520]	391000810
11	85.47 [3365]	80.01 [3150]	72.00 [2835]	391000811
12	93.47 [3680]	88.01 [3465]	80.00 [3150]	391000812

NOTES:

- 1. MATERIAL: SEE TABLE
- 2. FINISHES: SEE TABLE
- 3.'XX' REFERS TO THE NUMBER OF CIRCUITS
- 4. ASSEMBLY IS ROHS COMPLIANT BY EXEMPTION. COMPONENTS MARKED WITH AN ASTERISK (*) ARE ROHS COMPLIANT BY EXEMPTION, ALL OTHERS ARE ROHS COMPLIANT.

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH
4	XX*2	CLAMPING SCREWS, M2.6 (B)	STEEL	ZINC
3	XX	WIRE PROTECTOR	BRASS	NICKEL
2	XX	TERMINAL (*)	BRASS	NICKEL
1	1	INSULATOR	NYLON 6	CLEAR

REVISED & REDRAWN
 EC NO: WNA2010-0649
 DRAWN: CLYORK 2010/04/26
 CHECKED: DTITUS 2010/04/26
 APPROVED: DTITUS 2010/04/26

QUALITY SYMBOLS
 ▽=0
 ▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± .005
2 PLACES	± 0.13	± .010
1 PLACE	± 0.3	± ---
ANGULAR ± 2 °		

DRAFT WHERE APPLICABLE
 MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM/IN
 SCALE: 2:1
 DESIGN UNITS: INCH
 THIRD ANGLE PROJECTION
 DRAWN BY: CLYORK DATE: 2010/04/26
 CHECKED BY: DTITUS DATE: 2010/04/26
 APPROVED BY: DTITUS DATE: 2010/04/26
 MATERIAL NO.: SEE CHART
 SIZE: B

TITLE: 8MM PITCH HIGH PROFILE WITH WIRE PROTECTORS
 MOLEX INCORPORATED
 DOCUMENT NO.: SD-39100-002
 SHEET NO.: 1 OF 1
 THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION