

TF 7-4-VA-230AC/U

This item is no longer available. Should you have any questions, please contact our Sales Team.

Order No.: 2856401

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2856401>

Protective plug TF with varistors between 4 signal lines and earth, temperature-monitored with disconnect device, a path to accommodate fine fuses 5 x 20 mm, ground connection line. Nominal voltage: 230 V AC

Commercial data

GTIN (EAN)	4017918821302
Note	Made-to-order
sales group	J240
Pack	5 pcs.
Customs tariff	85363010
Weight/Piece	0.07534 KG

Product notes

WEEE/RoHS-compliant since:
06/07/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Housing material	PA
Inflammability class acc. to UL 94	V2
Standards for air and creepage distances	IEC 60664-1: 1992-10
	VDE 0110-1

Ambient temperature (operation)	-40 °C ... 80 °C
Degree of protection	IP20
Direction of action	Line-Line & Line-Earth Ground
Arrester can be tested with CHECKMASTER from software version:	From SW rev. 2.20

Protective circuit

Nominal voltage U_N	230 V AC (core-ground) 400 V AC (core-core)
Arrester rated voltage U_C (Core-Core)	440 V AC
Arrester rated voltage U_C (Core-Earth)	275 V AC
Nominal current I_N	3 A (80 °C)
Operating effective current I_C at U_C	$\leq 10 \mu\text{A}$
Ground conductor current I_{PE}	40 μA
Nominal discharge surge current I_n (8/20) μs (Core-Core)	2.5 kA
Nominal discharge surge current I_n (8/20) μs (Core-Earth)	2.5 kA
Max. discharge surge current I_{max} (8/20) μs maximum (Core-Core)	8 kA
Max. discharge surge current I_{max} (8/20) μs maximum (Core-Earth)	8 kA
Residual voltage at I_n , (conductor-conductor)	$\leq 2 \text{ kV}$
Residual voltage at I_n , (conductor-ground)	$\leq 1 \text{ kV}$
Energy absorption symmetrical	302 J
Energy absorption, asymmetrical	151 J
Protection level U_P (Core-Core)	$\leq 2 \text{ kV}$ (For $U_{OC} = 6 \text{ kV}$)
Protection level U_P (Core-Earth)	$\leq 1 \text{ kV}$ (For $U_{OC} = 6 \text{ kV}$)
Response time t_A (Core-Core)	$\leq 25 \text{ ns}$
Response time t_A (Core-Earth)	$\leq 25 \text{ ns}$
Frequency range	50 Hz ... 60 Hz
Capacity (Core-Core)	315 pF (typ.)
Capacity (Core-Earth)	630 pF (typ.)
Max. required back-up fuse	3 A

Connection data

Type of connection	ST-REL 7
--------------------	----------

Certificates / Approvals



Certification

GOST

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;