



SAW Components

SAW Tx Filter

R-GSM

Series/type:	B5057
Ordering code:	B39941B5057U410
Date:	March 22, 2007
Version:	2.0

© EPCOS AG 2007. Reproduction, publication and dissemination of this data sheet, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.




Application

- Low-loss filter for Basestation R-GSM, transmit path (Tx)
- Usable passband 39 MHz
- Unbalanced to unbalanced operation
- No matching required
- Filter impedance 50 Ω




Features

- Package size 3.0 x 3.0 x 1.1 mm³
- Package code DCC6C
- Approx. weight 0.037 g
- Ceramic package for **Surface Mount Technology (SMT)**
- RoHS compliant
- Ni, gold-plated
- **Electrostatic Sensitive Device (ESD)**



Pin configuration

- 2 Input
- 5 Output
- 1,3,4,6 To be grounded



Please read *cautions and warnings and important notes* at the end of this document.



Data Sheet



Characteristics

Temperature range for specification: $T = -30$ to $+80$ °C
 Terminating source impedance: $Z_S = 50 \Omega$
 Terminating load impedance: $Z_L = 50 \Omega$

		min.	typ. @ 25 °C	max.	
Center frequency	f_C	—	940.5	—	MHz
Maximum insertion attenuation	α_{max}	—	2.7	4.0 ¹⁾	dB
921.0 ... 960.0 MHz					
Amplitude ripple (p-p)	$\Delta\alpha$	—	1.4	3.0 ²⁾	dB
921.0 ... 960.0 MHz					
Input VSWR		—	2.3	3.0 ³⁾	
921.0 ... 960.0 MHz					
Output VSWR		—	2.6	3.0 ⁴⁾	
921.0 ... 960.0 MHz					
Attenuation	α				dB
0.3 ... 800.0 MHz		25	47	—	dB
800.0 ... 880.0 MHz		26	39	—	dB
880.0 ... 905.0 MHz		20 ⁵⁾	31	—	dB
905.0 ... 915.0 MHz		2 ⁶⁾	6	—	dB
980.0 ... 985.0 MHz		23	42	—	dB
985.0 ... 1005.0 MHz		30	34	—	dB
1005.0 ... 1025.0 MHz		30	34	—	dB
1025.0 ... 1760.0 MHz		27	34	—	dB
1760.0 ... 2000.0 MHz		28	32	—	dB
2000.0 ... 4000.0 MHz		18	23	—	dB

1) 3.0 dB at 25 °C.
 2) 2.0 dB at 25 °C.
 3) 2.8 at 25 °C.
 4) 2.8 at 25 °C.
 5) 28 dB at 25 °C.
 6) 3 dB at 25 °C.



SAW Components

B5057

SAW Tx Filter

940.5 MHz

Data Sheet



Maximum ratings


Operable temperature range	T	-40 / +85	°C	
Storage temperature range	T _{stg}	-40 / +85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	100 ¹⁾	V	machine model, 10 pulses
Input Power at 921.0 ... 960.0 MHz	P _{IN}	10	dBm	continuous wave

¹⁾ acc. to JESD22-A115A (machine model), 10 negative & 10 positive pulses.


Please read *cautions and warnings and important notes* at the end of this document.



Transfer function (narrowband)



Transfer function (wideband)




Please read *cautions and warnings and important notes* at the end of this document.

Data Sheet




Smith chart


S_{11} function




normal impedance: 50.00 Ω



S_{22} function



normal impedance: 50.00 Ω



**SAW Components****B5057****SAW Tx Filter****940.5 MHz**

Data Sheet

**References**

Type	B5057
Ordering code	B39941B5057U410
Marking and package	C61157-A7-A67
Packaging	F61074-V8168-Z000
Date codes	L_1126
S-parameters	B5057_NB.s2p B5057_WB.s2p
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com .

**Published by EPCOS AG
Surface Acoustic Wave Components Division
P.O. Box 80 17 09, 81617 Munich, GERMANY**

© EPCOS AG 2007. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.

7 March 22, 2007



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of passive electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of a passive electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of a passive electronic component.
3. The warnings, cautions and product-specific notes must be observed.
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as "hazardous")**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, CeraDiode, CSSP, PhaseCap, PhaseMod, SIFI, SIKOREL, SilverCap, SIMID, SIOV, SIP5D, SIP5K, TOPcap, UltraCap, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.